PolarChoice[™] Boundary Satellite wireless microphone

Flexibility Performance Compatibility



The new PolarChoice™ Boundary Satellite from Electro-Voice® is the most flexible wireless boundary microphone available today. This unique product provides the perfect solution for countless applications, while meeting the critical demands of contractors, consultants and rental houses everywhere.

As a member of the PolarChoice[™] family of microphones, the user can choose from four polar patterns (omnidirectional, cardioid, supercardioid and figure-8) via a simple four-position rotary switch, optimizing audio pick-up for any acoustic environment.

And like its older brother the PolarChoice[™] Satellite, the PolarChoice[™] Boundary Satellite works with any current EV® or Telex wireless bodypack transmitter: Simply install the bodypack into the custom-designed compartment under the mic housing for simple set-up and use. This design feature allows the user to choose the level of wireless performance required. Likewise, the beltpack can be easily removed, so the transmitter is not dedicated to wireless boundary operation only: Today the wireless beltpack can be used with the Boundary Satellite; tonight the same beltpack can be removed and used with a lavalier or headworn mic.

In addition, the PolarChoice[™] Boundary Satellite features a programmable mic mute switch. Choose between momentary or latching, and between pushto-talk, or push-to-mute operation. All this, and the great sound quality that the PolarChoice[™] podium mic product family is known for.



A first in the industry, the PolarChoice® Boundary Satellite offers selectable polar patterns, interchangeable beltpacks, and great sound quality, all in a compact, easy-to-use, and unobtrusive package. It provides the perfect solution for the changing demands of the contemporary boardroom, house of worship, or rental application.

SPECIFICATIONS:

Generation Element:	Dual condenser, back electret
Frequency Response:	50 Hz to 20,000 Hz (see chart)
Polar Patterns:	Omnidirectional, Cardioid, Supercardioid, Figure 8
Switches and Controls:	Top mounted momentary membrane switch Push on/off, or push-to-mute selector. Power up on/off selector, High-pass en- able. 4-position polar pattern selector.
Sensitivity, Open Circuit Voltage, 1 kHz:	17.8 mV/Pascal
Clipping Level (1% THD):	>130 dB SPL
Equivalent Noise:	<26 dB SPL "A" weighted (0 dB=20 micropascals) Dynamic Range: >98 dB
Output Impedance, 1 kHz:	1000 ohms
Power Requirements:	5 VDC, supplied by optional bodypack
Current Consumption:	< 1.5 mA
Polarity:	Pin 2 positive, referenced to pin 1, with positive pressure on the diaphragm
Dimensions: (Without bodypack)	140.8mm (5.5") long, 81.2mm (3.2") wide, 50.3mm (2.0") high
Weight: (Without bodypack)	128 grams (4.5 oz.)



PA#20678

 Americas
 F

 Telex Communications Inc.
 F

 12000 Portland Ave South,
 A

 Burnsville, MN 55337, USA
 F

 USA—Phone: 1-800-392-34947, Fax: 1-800-955-6831
 F

 Canada—Phone: 1-866-505-5551, Fax: 1-866-336-8467
 Latin America—Phone: 1-952-887-5532, Fax: 1-952

 Tode-4212
 Za6-4212
 Za6-4212

Europe, Africa & Middle-East Germany: EVI Audio GmbH, Hirschberger Ring 45, D-94315, Straubing, Germany Phone: +49 9421 706-0, Fax: +49 9421 706-265 France: EVI Audio France S.A., Parc de Courcerin, Allée Lech Walesa, F 77185 Lognes, France Phone: +33 1-6480-0090 Fax: +33 1-6006-5103 UK: Shuttlesound, 4 The Willows Centre, Willow Lane, Mitcham,

Surrey CR4 4NX, UK Phone: +44 208 646 7114 Fax: +44 208 254 5666 Asia & Pacific Rim Japan: EVI Audio Japan Ltd. 5-3-8 Funabashi, Setagaya-Ku, Tokyo, Japan 156-0055 Phone: +81 3-5316-5020, Fax: +81 3-5316-5031

China: Telex EVI Audio (Shanghai) Ltd. Room 2210-2215, Tower B, Far East International Plaza, No. 317, Xianxia Road, Shanghai, China, PC: 200051 Phone: +86 21-6235-1677 Fax: +86 21-6235-1676 Hong Kong: Telex EVI Audio (HK) Ltd. Unit 5,1/F, Topsail Plaza 11 On Shum Street Shek Mun,Shatin HK Phone: +852 2351-3628, Fax: +852 2351-3329

Singapore: Telex Pte. Ltd. 3015A Ubi Road 1, 05-10 Kampong Ubi Industrial Estate, Singapore 408705 Phone: +65 6746-8760, Fax: +65 6746-1206

