



FCS-5092 Version: 1

1 Power supply unit is to be ordered separately.

# Fixed IP Network Camera, H.265/264, 5-Megapixel, 802.3af PoE, IR LEDs, Indoor/Outdoor

The LevelOne FCS-5092 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 5-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-5092 should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

# **Key Features**

- 5-Megapixel high-definition resolution
- Video compression: H.264/H.265
- Built-in infrared LEDs for night viewing up to 50m
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- IEEE 802.3af PoE compliant to simplify deployment and installation
- Weatherproof IP67-rated housing
- Built-in Micro SDHC/SDXC card slot for local storage

# **Specifications**

# **System Specifications**

### Standards & Protocols:

TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP,SMTP, SNMP, IGMP, 802.1X, QoS, IPv6

## Image Sensor:

1/2.9" Progressive Scan CMOS

#### Lens:

Fixed-focal, f=4mm,F2.0

#### Port

1 x RJ-45 10/100 Mbps PoE port Power Connector 1 x MicroSDHC/ MicroSDXC card slot

## Button/Knob:

Reset Button

# Indicator:

Power

www.level1.com Page 1 of 4

#### IR Cut Filter:

Removable infrared-cut filter for day & night function

#### IR LED:

IR LEDs for illumination up to 50m

#### Shutter Time:

 $1/3 \sim 1/10.000 \text{ sec}$ 

#### Angle of View:

63.5°

#### Video Compression:

H.265, H.264

#### Resolution:

50Hz: 20 fps (2560  $\times$  1656), 25 fps 2560  $\times$  1440, 2048  $\times$  1536, 1920  $\times$  1080, 1280  $\times$ 720) 60Hz: 20 fps (2560  $\times$  1656), 30 fps 2560  $\times$  1440, 2048  $\times$  1536, 1920  $\times$  1080, 1280  $\times$ 720)

#### Video Format:

AVI

# Power Input:

12 VDC, 7 W; PoE, 9 W

#### Power Consumption:

7-9 W

## Data Transfer Rate:

32 Kbps to 16 Mbps

## **Features**

#### General:

rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser.

#### PoE:

PoE(802.3af, class 3)

#### Security:

One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter

## Management:

Behavior Analysis: Line crossing detection, intrusion detection, unattended baggage detection, object removal detection

Line Crossing Detection: Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported Intrusion Detection: Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported

Object Removal Detection: Objects removed from the pre-defined region, such as the exhibits on display. Unattended Baggage Detection: Objects left over in the pre-defined region such as the baggage, purse, dangerous materials

Face Detection: Human face appears in the image can be detected and trigger linkage method.

#### Video

Support 1 fixed region for mainstream and sub stream separately

## **Performance**

#### Number of Clients:

16

# Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

www.level1.com Page 2 of 4

## Frame Rate (fps):

2560 x 1656 @ 20fps

#### Minimum illumination:

Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR

# Environment

## Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

# Humidity (Non-condensing):

Humidity 95%

# Physical Specifications

# Dimensions (W x D x H mm):

?104.8 × 299.7 mm (?4.13? × 11.8?)

# Weight (g):

1200 g (2.65 lb.)

## Color:

White

# **Approval and Compliance**

## EMI/EMS:

CE/FCC

#### **Environmental Test:**

IP67

# Others:

ONVIF

# Others

# Viewing Systems:

Windows 7/8/10

# Compatibility:

IE Browser 9 above

# **Order Information**

FCS-5092

# **Package Contents**

FCS-5092

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

# **Optional Accessory**



## **CAS-7303**

Pole Mount Bracket, Clamping Range 2.6"-5"

www.level1.com Page 3 of 4



CAS-7307 Corner Mount Bracket



**CAS-7311**Junction box for Bullet Camera



**CAS-7312**Power Intake Box for Bullet Camera

www.level1.com Page 4 of 4