

PARAMETERS

Impedance	8 ohms
Re	7.6 ohms
Le	0.58 mH @ 1 kHz
Fs	1276 Hz
Qms	N/A
Qes	N/A
Qts	1.25
Mms	0.26 g
Cms	0.0002 mm/N
Sd	N/A
Vd	N/A
BL	1.12 Tm
Vas	N/A
Xmax	N/A
VC Diameter	25 mm
SPL	N/A
RMS Power Handling	10 watts
Usable Frequency Range (Hz)	N/A


FEATURES

- Designed for extreme outdoor environments where normal speakers cannot go
- 3M™ VHB™ adhesive disc for secure, fast placement
- IP67 rated watertight enclosure
- Includes a 68" wiring harness

APPLICATIONS


- Invisible home theater and multi-room audio
- Electronic gaming machines
- Advertising signage
- Point-of-purchase displays
- Multimedia exhibits
- Commercial distributed audio
- Kiosks
- Automotive audio
- Bathroom tubs and showers

IMPEDANCE/PHASE



Measurement taken with transducer uncoupled facing upward.

FREQUENCY RESPONSE



OmniMic

1/3rd octave smoothing - measurement taken with transducer adhered off-center on a 12" x 12" x 1/2" foam core board in an infinite baffle setup.

Note: This information is for comparison purposes only, the actual frequency response will depend on many factors of which the diaphragm being the greatest contributor.