# LC6-SW100-L Ceiling Mount Subwoofer White

www.boschsecurity.com





- ► Quick-install design with captive mounting tabs to fit nearly any ceiling construction.
- ► Five 2-pin Phoenix connectors for wiring subwoofer and satellite speakers.
- ▶ UL 2043/1480 ratings allow for use in signaling applications and plenum air spaces.
- ► Ceiling cutout template and all mounting accessories included.
- ► Available in white finish.

The LC6-SW100-L is ideal for background and foreground music systems for restaurants, bars, patios, retail, and other applications. The LC6-SW100-L consists of a high performance ceiling mount 8-inch subwoofer module with a crossover network to support four (4) ceiling mount LC6-S-L 2-inch satellite speakers. The system provides for easy signal connections at the subwoofer and can support either 4 ohm or 70/100v signal connections. Its high power handling allows the LC6-SW100-L to be used in a wide variety of environments and spaces to provide high quality background or foreground music.

# **Certifications and approvals**

Region	Certification
Europe	CE

# Parts included

Quantity	Description
1	Ceiling mount subwoofer
2	Tile rails
1	C-ring support
1	Grille
1	Installation manual
2	screws
1	Cutout template
1	Paint shield

<sup>\*</sup> Ceiling Mount Subwoofer (1 box)


## **Technical specifications**

Frequency Response (-10 dB):	45 Hz - 300 Hz <sup>1</sup>
Power Handling:	200 W <sup>2</sup>


$88\mathrm{dB^1}$
mono 4 ohm
114 dB
Omnidirectional
Omnidirectional
200 mm (7.87 in)
Phoenix (2-pin)
Steel & ABS (fire rated)
100 W, 50 W, 25W, 12.5W
316 mm x 373 mm (12.44 in x 14.69 in)
346 mm (13.6 in)
9.52 kg (21 lb)
12.72 kg (28 lb)
C-Ring, Tile Rails

<sup>&</sup>lt;sup>1</sup>Half space.

## Frequency Response:



#### **Dimensions:**



# **Ordering information**

LC6-SW100-L Ceiling Mount Subwoofer White Ceiling mount subwoofer - white finish Order number LC6-SW100-L

### Represented by:

Bosch Security Systems, Inc. 12000 Portland Avenue South Burnsville MN 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschsecurity.com

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2699 apr.securitysystems@bosch.com www.boschsecurity.asia

Bosch (Shanghai) Security Systems Ltd. Robert Bosch Ltda Security Systems Division 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398

Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 latam.boschsecurity@bosch.com www.boschsecurity.com

<sup>&</sup>lt;sup>2</sup>Long Term Program Rating, 3 dB greater than continuous noise pink noise rating.