

Plena All-in-One Wall Panel

www.boschsecurity.com



BOSCH
Invented for life



- ▶ Remote control for the Plena All-in-One Unit PLN-6AIO240
- ▶ BGM routing and volume control
- ▶ Remote selection of four music source inputs
- ▶ Remote microphone/line input
- ▶ Powered from the Plena All-in-One Unit

The Plena Wall Panel PLN-4S6Z is used to control the source selection, zone selection, and volume of the Plena All-in-One Unit PLN-6AIO240 from a remote location, and accepts a microphone or music source.

System overview

The Wall Panel is connected to the Plena All-in-One Unit PLN-6AIO240 with a standard Cat-5 cable. The maximum cable length is 600 m. The buttons on the Wall Panel have the same function as the corresponding buttons on the front panel of the All-in-One Unit. The design and color of the Wall Panel are unobtrusive in any interior. Ease of installation, operation, and reliability are optimized in the design.

Functions

Remote zone and music source control

Six zones and four music input sources can be selected from a remote location. The Enable button on the front of the Wall Panel can be pressed to gain instant remote control over the music selection and master volume.

Indicators

The ON status of each zone and selected music source is indicated by an LED.

Connections and settings

The Wall Panel can be easily and quickly connected to the Plena All-in-One Unit, by using a Cat-5 cable and RJ45 connectors. Configuration is not necessary.

Control and indicators

Front side:

- Selection buttons for six zones with All-call
- Music source selection button
- Master volume control
- Enable button
- Level control for local audio input

Interconnections

- XLR connector for microphone
- 3.5 mm stereo connector for music source
- RJ45 connector (inside Wall Panel)

Certifications and approvals

Safety	IEC/EN 60065
EMC	EN 55103-1 EN 55103-2 EN 61000-3-2 EN 61000-3-3
Environment	EN 50581

US	UL 60065 FCC Part 15B
CA	CSA C22.2.60065
CN	CCC
AU/NZ	C-Tick

Region	Certification
Europe	CE

Installation/configuration notes

Remote control

The Wall Panel can be attached to a wall or flat surface by use of the holes in the rear mounting bracket. It is powered from the Plena All-in-One Unit and uses a single Cat-5 cable for interconnection up to 600 m from the All-in-One Unit. No configuration is needed.

Parts included

Quantity	Component
1	All-in-One Wall Panel
1 m	Cat-5 cable with RJ45 plugs

Technical specifications

Electrical

Power supply	
Voltage range	24 Vdc, supplied by the connected amplifier
Current consumption (typical)	<50 mA
Connector	1 x RJ45 socket (inside Wall Panel)

Mechanical

Dimensions (H x W x D)	115 x 115 x 70 mm (4.5 x 4.5 x 2.8 in)
Weight	Approx. 0.6 kg (1.3 lb)

Environmental

Operating temperature	-10°C to +45°C (14°F to +113°F)
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Relative humidity	<95% (non-condensing)

Ordering information

Plena All-in-One Wall Panel

Wired remote control for the Plena All-in-One Unit with local audio inputs.

Order number **PLN-4S6Z**

Represented by:

Americas:

Bosch Security Systems, Inc.
12000 Portland Avenue South
Burnsville MN 55337, USA
Phone: +1-800-392-3497
Fax: +1-800-955-6831
audiosupport@us.bosch.com
www.boschsecurity.com

Europe, Middle East, Africa:

Bosch Security Systems B.V.
P.O. Box 80002
5617 BA Eindhoven, The Netherlands
Phone: + 31 40 2577 284
Fax: +31 40 2577 330
emea.securitysystems@bosch.com
www.boschsecurity.com

Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security
Systems
11 Bishan Street 21
Singapore 573943
Phone: +65 6571 2808
Fax: +65 6571 2699
apr.securitysystems@bosch.com
www.boschsecurity.asia

China:

Bosch (Shanghai) Security Systems Ltd.
201 Building, No. 333 Fuquan Road
North IBP
Changning District, Shanghai
200335 China
Phone +86 21 22181111
Fax: +86 21 22182398
www.boschsecurity.com.cn

America Latina:

Robert Bosch Ltda Security Systems Division
Via Anhanguera, Km 98
CEP 13065-900
Campinas, Sao Paulo, Brazil
Phone: +55 19 2103 2860
Fax: +55 19 2103 2862
latam.boschsecurity@bosch.com
www.boschsecurity.com