



AC Motor Start Capacitors

MOTOR START CAPACITORS - CHASSIS MOUNT

DUAL 6.35mm TAGS or FLY LEADS with INSULATED BOLT

Non-Inductive construction Self-Healing property.
 Flame-Retardant Plastic & Epoxy.
 High Moisture-Resistance.
 Temp -40°C to +85°C.
 Tolerance ±10%.
 Short term Over-Voltage tolerant.
 Quality Assurance Premium production.
 As used in Air conditioners, etc. motor start, motor run,
 across line, and many other mains applications.

Suntan®

Value	Volts	Type	Size	Code
1µF	450V	6.4mm	30x57mm	1WTR450
2µF	450V	6.4mm	30x57mm	2WTR450
2.5µF	450V	6.4mm	30x57mm	2.5WTR450
3µF	450V	6.4mm	30x57mm	3WTR450
3.5µF	450V	6.4mm	30x57mm	3.5WTR450
4.5µF	450V	6.4mm	30x57mm	4.5WTR450
5µF	450V	6.4mm	30x57mm	5WTR450
6µF	450V	6.4mm	30x57mm	6WTR450
7µF	450V	6.4mm	35x65mm	7WTR450
8µF	450V	6.4mm	35x65mm	8WTR450
10µF	450V	6.4mm	35x65mm	10WTR450
12µF	450V	6.4mm	40x70mm	12WTR450
14µF	450V	6.4mm	40x70mm	14WTR450
16µF	450V	6.4mm	35x65mm	16WTR450
18µF	450V	6.4mm	40x70mm	18WTR450
20µF	450V	6.4mm	40x75mm	20WTR450
25µF	450V	6.4mm	40x75mm	25WTR450
30µF	450V	6.4mm	45x95mm	30WTR450
35µF	450V	6.4mm	45x95mm	35WTR450
40µF	450V	6.4mm	50x105mm	40WTR450
50µF	450V	6.4mm	50x105mm	50WTR450
60µF	450V	6.4mm	50x116mm	60WTR450



Value	Volts	Type	Size	Code
30µF	450V	Fly Lead	45x98mm	30WPR450
50µF	450V	Fly Lead	50x109mm	50WPR450



3WTR450



10WTR450



30WPR450



35WTR450



25WTR450



50WPR450

