

# Cable Tidy Solutions

## REMOVE THE CLUTTER OF CABLES

D-Line decorative trunking blends with decor so cables disappear. D-Line cable covers are easy to fit, and look great on any surface. A popular solution in the UK, now available from WES in Australia.





## About D-Line

**D-Line is a UK company, based in Newcastle upon Tyne, with a global reputation for innovative cable management products 'for use where time, safety and appearance matter'.**

In 2004 D-Line patented the world's fastest trunking system, in subtle shapes to blend with modern decor. These iconic D-shaped ½ round & ¼ round profiles are now popular in 25+ countries. As often said 'the finishing touch of a D-Line installation creates a lasting impression'; preferred by specifiers, installers and clients.

In 2009 D-Line also invented the first fire-rated clips that could be fitted in non-metallic trunking, so preventing the potentially fatal consequences of cable entanglement.

In 2010 D-Line developed Socket Enclosures to contain socket extensions and cable clutter, and in 2014 pioneered linkable Floor Cable Protectors to satisfy another common requirement.

In 2016 D-Line launched The Cable Safety at Work Campaign - advising of cable-hazards, legislative responsibilities, and preventive product solutions to reduce accidents by addressing Health & Safety cable-risks in workplaces.

In 2018 D-Line's Safe-D range of fire rated fixings evolved to include one-piece one-fixing Conduit Clips, F-Clips (flat, flexible & fire rated), Spring Clips to hold cables in Micro Trunking, the fire rated D-Fixing screw and more!

D-Line products are manufactured in the UK to most exacting standards. They are fully tested and certified to highest quality requirements.

“ D-Line trunking is our preferred way to route cables... compared to chasing walls, or standard mini-trunking, it makes a better choice all round! ”



*The modern way to hide cables...*



# About D-Line Trunking

The World's Fastest Trunking System



## The modern way to hide cables...



**D-shaped and linear, D-Line is named after the iconic style of our first products. The single-piece design, complementary accessories and subtle shapes combine so that D-Line trunking is 'quick to install and looks great!'**

Compared to channelling walls or lifting floors to contain cables, D-Line appreciate how surface trunking installations can save huge amounts of time and cost, while minimising inconvenience; and thereafter protect cables for on-going peace of mind.












It follows that D-Line trunking is an inexpensive and practical alternative to **either** channelling walls **or** traditional trunking products.

At D-Line we respect also that for I.T. and Datacoms, electrical upgrades, Fire & Security, and many HVAC

and Audio Visual projects, the equipment will often be the most costly expenditure, but, for a surface installation, the trunking will usually be the most conspicuous element...

D-Line enables a quality of finish to complement the interior design of modern spaces, in stylish ways that are obvious to all stakeholders. As often said using D-Line cable trunking 'cables seem to disappear' and 'the finishing touch of a D-Line cable management installation makes a lasting impression.'

Choose from eight profiles according to the volume of cables to be contained. A choice of colours and full ranges of accessories are available also.

	FEATURE	BENEFIT
	<b>Designer shapes and colours</b>	<ul style="list-style-type: none"> <li>• Designs give subtle appearance with no sharp edges; to blend with contemporary surrounds - or colour options to provide a striking feature!</li> </ul>
		<ul style="list-style-type: none"> <li>• Alternative sizes satisfy popular demands Available as (width x height) 16x8mm, 20x10mm, 30x15mm &amp; 50x25mm</li> <li>• Gentle on impact and easy to clean</li> </ul>
		<ul style="list-style-type: none"> <li>• Available (width x height) 22x22mm &amp; 30x30mm</li> <li>• 22x22mm makes the ultimate floor trim!</li> <li>• Can also be used as cornice or coving</li> </ul>
	<b>PVC</b>	<ul style="list-style-type: none"> <li>• Self extinguishing</li> <li>• UV stabilised</li> <li>• Lightweight &amp; easy to cut</li> <li>• Stable between -30°C to +60°C</li> <li>• Satisfies BS EN 50085-1:2005</li> </ul>
	<b>Patented hinge &amp; click-lock lid</b>	<ul style="list-style-type: none"> <li>• Single-piece design... for quick &amp; easy handling</li> <li>• Only one cut (no need to separately cut base, and lid, before fitting accessories)</li> <li>• Lids will never peel or detach - maintenance friendly</li> <li>• Tensioned hinge provides a cable retainer to keep cables in position during installation</li> <li>• Easy to later add or remove cables</li> <li>• User friendly in tight spaces</li> <li>• Hinge acts as a shock absorber on impact</li> </ul>
	<b>Film covered lengths</b>	<ul style="list-style-type: none"> <li>• Keeps lengths pristine before installation</li> <li>• Environmentally friendly packaging</li> </ul>
	<b>Self-adhesive foam backing</b>	<ul style="list-style-type: none"> <li>• Simply peel &amp; stick - Quick &amp; easy to install</li> <li>• Can be drilled also</li> </ul>
	<b>Easy to use Ratchet Cutting Tool</b>	<ul style="list-style-type: none"> <li>• Use to cut up to 40mm wide D-Line Trunking</li> <li>• No dust residue</li> <li>• Quick &amp; clean cutting action</li> </ul>
	<b>Paintable</b>	<ul style="list-style-type: none"> <li>• Can blend with any decor</li> </ul>



### When 20,000 hotel rooms needed to hide cables for new heating controllers, D-Line Mini Trunking proved the perfect choice...

**Using D-Line saved a small fortune compared to the cost of channelling the walls, then needing to co-ordinate works to re-plaster and re-decorate.**

Aside the noise and disruption, trying to recess the cabling would have put rooms out-of-service. However traditional trunking did not look suitable for a hotel chain with a reputation for comfort and style.

Cables from wall mounted heaters to wall mounted controllers were concealed in D-Line Mini Trunking which blended with the skirting, and, when necessary, up-and-around bedheads.

A cut-length rose up to the heater via a Clip-Over Equal Tee, while Clip-Over Internal Bends made internal corner connections quick and easy. The Flat Bend required was the Smooth-Fit version, as the secure internal tabs were

favoured to eliminate future maintenance concerns, given that this part was most likely to be bumped by guests' baggage.

The ½ round shape of the length rising up to the wall-mounted controller was preferred also for its impact resistance, the lack of sharp edge a distinct benefit (compared to traditional sharp edge trunking).

The D-Line Cutting Tool was used throughout, saving time and leaving no PVC dust residue.

The self-adhesive tape was used to attach the lengths to the walls, with a screw-fixing and plug then inserted 750mm from each end.

The result was 20,000 installations using 200km - all easy to fit, quick to install and blending with decor.

**Further details on request.**

#### Unique Clip-Over Accessories



#### Saves Channelling Walls













#### Quick and Easy to Fit





## Trunking Guide

Cross-reference Table with WES Order Codes of the most popular items. RETAP codes represent Kits available including these parts.

shape & size							
(wxh)	60x30mm	50x25mm	40x20mm	30x15mm	16x8mm	22x22mm	30x30mm
<b>Trunking Lengths</b>		<b>Large</b>		<b>Mini</b>	<b>Micro</b>	<b>Quad22</b>	
1m Length [White]		1D5025W/EH					
1m Length [Black]		1D5025B/EH					
1.5m Length							
2m Length [White]				D23015WSA	D21608WSA	D222QSWSA	
3m Length							
Self Adhesive Divider(white)							
<b>Clip Over Accessories</b>							
Flat Bend							
Internal Bend							
External Bend							
Equal Tee							
Door Top Bend							
Inlet/Outlet Coupler (22x22 only)							
<b>Smooth Fit Accessories</b>							
Flat Bend				RETAP3015W	RETAP1608W		
Internal Bend				RETAP3015W	RETAP1608W	RETAP22QSW	
External Bend				RETAP3015W	RETAP1608W	RETAP22QSW	
Equal Tee					RETAP1608W		
Cable Outlet				RETAP3015W		RETAP22QSW	
Cable Inlet						RETAP22QSW	
Reducing Tee(to 30x15mm)							
Coupler				RETAP3015W	RETAP1608W	RETAP22QSW	
End Cap				RETAP3015W	RETAP1608W	RETAP22QSW	
End Cap Left(¼ round only)							
End Cap Right(¼ round only)							
Corner Tee							
Box Adaptor Tee							
30x15mm Box Adaptor							
Pattress Adaptor							
Circular Adaptor							
<b>Other Accessories</b>							
FCLIP (BS5839 part 1)							
Ratchet Cutting Tool							
28mm Single Surface box							
28mm Twin Surface box							
35mm Single Surface box							
35mm Twin Surface box							



### Clip Over Accessories



### Smooth Fit Accessories




## How Clip-Over Accessories Work



## ½ Round Clip Over Accessories (30x15mm only)

**Internal Bend**



**External Bend**



**Flat Bend**



**Equal Tee**



**Door Top Bend**



## ½ Round Smooth Fit Accessories (RETAP Series Of Kits)

**Internal Bend**



**External Bend**



**Flat Bend**



**Equal Tee**



**Coupler**




**End Cap**



**Circular Adaptor**



**Patress Adaptor**



**Cable Inlet/Outlet**



**Box Adaptor**



**Box Adaptor Tee**



**Reducing Tee**



## ¼ Round Clip Over Accessories (22x22mm only)

**Internal Bend**



**External Bend**




**Cable Inlet/Outlet**



## ¼ Round Smooth Fit Accessories (RETAP Series Of Kits)

**Internal Bend**



**External Bend**



**Cable Inlet**




**Cable Outlet**



**Connector**



**End Cap**



## Other Accessories

**Single Surface Socket Box**



**Twin Surface Socket Box**



**FCLIP**




D-LINE



## Micro Trunking

Feature	Comment
PVC base & lid	<ul style="list-style-type: none"><li>• Light weight, easy to handle &amp; cut</li><li>• Self-extinguishing</li><li>• Can be drilled</li></ul>
Elastomer hinge	<ul style="list-style-type: none"><li>• Effectively bonds base &amp; lid</li><li>• Lid cannot detach</li><li>• Low-maintenance</li><li>• Keeps cables in place during installation</li><li>• Impact absorbing</li><li>• Can be opened &amp; closed thousands of times</li></ul>
Available Colours	• White • Magnolia • Black • Aluminium Effect • Wood Effect
UV stabilised	• Will not discolour or turn brittle in sunlight
Operating temperature	• Stable between -30°C upto +60°C
½ round design	<ul style="list-style-type: none"><li>• No sharp edges</li><li>• Enables subtle aesthetics</li><li>• Blends above skirting</li></ul>
External Dimensions	<ul style="list-style-type: none"><li>• The smallest profile</li><li>• 16x8mm (w x h) aka Micro</li></ul>
Popular usages	• To contain wires e.g. low-voltage, telephone cables, speaker wires, alarm cables
Tape	<ul style="list-style-type: none"><li>• Foam backed 1mm thick</li><li>• Effective on clean dry surfaces</li><li>• Caution, can spoil surfaces on removal</li></ul>
Can be painted	• Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	<ul style="list-style-type: none"><li>• 1.54 lbs per ft</li><li>• 0.7 kg per metre</li></ul>
Packaging	• Each length supplied with removable film cover
Capacity	• If containing 240v cords leave 45% of internal capacity for air circulation
Accessories Available	• Yes (Smooth-Fit style)
Quality approvals	• BS EN 50085 - 1:2005 Part 1



**D-LINE**

## Mini Trunking

Feature	Comment
PVC base & lid	<ul style="list-style-type: none"> <li>• Light weight, easy to handle &amp; cut</li> <li>• Self-extinguishing</li> <li>• Can be drilled</li> </ul>
Elastomer hinge	<ul style="list-style-type: none"> <li>• Effectively bonds base &amp; lid</li> <li>• Lid cannot detach</li> <li>• Low-maintenance</li> <li>• Keeps cables in place during installation</li> <li>• Impact absorbing</li> <li>• Can be opened &amp; closed thousands of times</li> </ul>
Available Colours	• White • Magnolia • Black • Aluminium Effect • Wood Effect
UV stabilised	• Will not discolour or turn brittle in sunlight
Operating temperature	• Stable between -30°C upto +60°C
½ round design	<ul style="list-style-type: none"> <li>• No sharp edges</li> <li>• Enables subtle aesthetics</li> <li>• Blends above skirting</li> </ul>
External Dimensions	• 30x15mm (w x h) aka Mini
Popular usages	<ul style="list-style-type: none"> <li>• For satellite, aerial &amp; broadband cables; for surface switch and socket installations</li> <li>• Cable drops, above skirting tops and across ceilings; for lighting and smoke alarm installations</li> </ul>
Tape	<ul style="list-style-type: none"> <li>• Foam backed 1mm thick</li> <li>• Effective on clean dry surfaces</li> <li>• Caution, can spoil surfaces on removal</li> </ul>
Can be painted	• Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	<ul style="list-style-type: none"> <li>• 0.33 lbs per ft</li> <li>• 0.15 kg per metre</li> </ul>
Packaging	• Each length supplied with removable film cover
Capacity	<ul style="list-style-type: none"> <li>• If containing 240v cords leave 45% of internal capacity for air circulation</li> <li>• Can contain up to: <ul style="list-style-type: none"> <li>- 2x 1.5mm Twin &amp; Earth</li> <li>- 2x 2.5mm Twin &amp; Earth</li> <li>- 2x 2c 1.5mm Fire Performance Cables</li> <li>- 4x Cat 5 cables</li> <li>- 3x 1.5m 3c flex cables</li> <li>- F-Clips</li> </ul> </li> </ul>
Accessories Available	• Yes, Smooth-Fit or Clip-Over options
Quality approvals	• BS EN 50085 - 1:2005 Part 1



## TV Trunking

Feature	Comment
PVC base & lid	<ul style="list-style-type: none"> <li>• Light weight, easy to handle &amp; cut</li> <li>• Self-extinguishing</li> <li>• Can be drilled</li> </ul>
Elastomer hinge	<ul style="list-style-type: none"> <li>• Effectively bonds base &amp; lid</li> <li>• Lid cannot detach</li> <li>• Low-maintenance</li> <li>• Keeps cables in place during installation</li> <li>• Impact absorbing</li> <li>• Can be opened &amp; closed thousands of times</li> </ul>
Available Colours	• White • Magnolia • Black • Aluminium Effect • Wood Effect
UV stabilised	• Will not discolour or turn brittle in sunlight
Operating temperature	• Stable between -30°C upto +60°C
½ round design	<ul style="list-style-type: none"> <li>• No sharp edges</li> <li>• Enables subtle aesthetics</li> </ul>
External Dimensions	• 50x25mm (w x h) aka TV Drop
Popular usages	• Hide cables from wall-mounted TVs; Hide cables on underside of desktops and up desk legs
Tape	<ul style="list-style-type: none"> <li>• Foam backed 1mm thick</li> <li>• Effective on clean dry surfaces</li> <li>• Caution, can spoil surfaces on removal</li> </ul>
Can be painted	• Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	<ul style="list-style-type: none"> <li>• 0.6 lbs per ft</li> <li>• 0.27 kg per metre</li> </ul>
Packaging	• Each length supplied with removable film cover
Capacity	<ul style="list-style-type: none"> <li>• If containing 240v cords leave 45% of internal capacity for air circulation</li> <li>• Can contain up to 6+ popular TV cables</li> </ul>
Accessories Available	• Yes (Smooth-Fit style)
Quality approvals	• BS EN 50085 - 1:2005 Part 1




## 60x30mm Trunking

Feature	Comment
PVC base & lid	<ul style="list-style-type: none"> <li>• Light weight, easy to handle &amp; cut</li> <li>• Self-extinguishing</li> <li>• Can be drilled</li> </ul>
Elastomer hinge	<ul style="list-style-type: none"> <li>• Effectively bonds base &amp; lid</li> <li>• Lid cannot detach</li> <li>• Low-maintenance</li> <li>• Keeps cables in place during installation</li> <li>• Impact absorbing</li> <li>• Can be opened &amp; closed thousands of times</li> </ul>
Available Colours	• White • Magnolia • Black • Aluminium Effect
UV stabilised	• Will not discolour or turn brittle in sunlight
Operating temperature	• Stable between -30°C upto +60°C
½ round design	<ul style="list-style-type: none"> <li>• No sharp edges</li> <li>• Enables subtle aesthetics</li> </ul>
External Dimensions	• 60x30mm (w x h) - our largest profile!
Popular usages	• Hide cables from wide screen wall-mounted TVs
Tape	<ul style="list-style-type: none"> <li>• Foam backed 1mm thick</li> <li>• Effective on clean dry surfaces</li> <li>• Caution, can spoil surfaces on removal</li> </ul>
Can be painted	• Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	• 0.39 kg per metre
Packaging	• Each length supplied with removable film cover
Capacity	<ul style="list-style-type: none"> <li>• If containing 240v cords leave 45% of internal capacity for air circulation</li> <li>• Can contain up to 8+ popular TV cables</li> </ul>
Accessories Available	• Yes (Smooth-Fit style)
Quality approvals	• BS EN 50085 - 1:2005 Part 1



D-LINE



Light Oak Effect



Stainable



Wood Effect













## 1/4-Round Floor Trim

Feature	Comment
PVC base & lid	<ul style="list-style-type: none"><li>• Light weight, easy to handle &amp; cut</li><li>• Self-extinguishing</li><li>• Can be drilled</li></ul>
Elastomer hinge	<ul style="list-style-type: none"><li>• Effectively bonds base &amp; lid</li><li>• Lid cannot detach</li><li>• Low-maintenance</li><li>• Keeps cables in place during installation</li><li>• Impact absorbing</li><li>• Can be opened &amp; closed thousands of times</li></ul>
Available Colours	• White • Light Oak Effect • Stainable • Wood Effect
UV stabilised	• Will not discolour or turn brittle in sunlight
Operating temperature	• Stable between -30°C upto +60°C
1/4 round design	<ul style="list-style-type: none"><li>• No sharp edges</li><li>• Enables subtle aesthetics</li><li>• For horizontal (&amp; vertical) 90 degree intersections</li></ul>
External Dimensions	• 22x22mm (w x h)
Popular usages	<ul style="list-style-type: none"><li>• Covers expansions gaps around floor edges</li><li>• Indoors as Floor Trim; for Worktops; Corner drops</li></ul>
Tape	<ul style="list-style-type: none"><li>• Foam backed 1mm thick</li><li>• Effective on clean dry surfaces</li><li>• Caution, can spoil surfaces on removal</li></ul>
Can be painted	• Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	<ul style="list-style-type: none"><li>• 0.33 lbs per ft</li><li>• 0.15 kg per metre</li></ul>
Packaging	• Each length supplied with removable film cover
Capacity	• If containing 240v cords leave 45% of internal capacity for air circulation
Accessories Available	• Yes, including Clip-Over bends & Inlet/Outlet Connector
Quality approvals	• BS EN 50085 - 1:2005 Part 1

# Clip-Over Accessories for ½ Circle Trunking

Feature	Comment
Rear Grip Tabs	• Hold Accessory in 1mm gap between flat surface and D-Line length, as made possible by depth of rear foam-tape
Abs material	• Robust material
Can be painted	• Scuff using gentle abrasive such as fine sandpaper, so paint keys for best results
Popular usage	• Available for Mini (30x15mm)
Easy-to-install	• Clip-Over style can forgive poor cuts at length ends, and imprecise measuring so saving installation time













Accessory Name	Description	Weight
<b>Internal Bend</b>  	<ul style="list-style-type: none"> <li>• Join lengths around 90 degree inside corners (30x15mm profile only)</li> </ul>	4g
<b>External Bend</b>  	<ul style="list-style-type: none"> <li>• Join lengths around 90 degree outside corners (30x15mm profile only)</li> </ul>	3g
<b>Flat Bend</b>  	<ul style="list-style-type: none"> <li>• Use between 2 lengths that change direction by 90 degrees on flat surfaces (30x15mm profile only)</li> </ul>	3g
<b>Equal Tee</b>  	<ul style="list-style-type: none"> <li>• Use to clip over 3 lengths of same profile (30x15mm profile only)</li> </ul>	3g
<b>Door Top Bend</b>  	<ul style="list-style-type: none"> <li>• Use to clip over interface of vertical and horizontal lengths (30x15mm profile only)</li> </ul>	4g

Accessory Name	Description	Weight
Internal Bend	<ul style="list-style-type: none"><li>• Join lengths on flat surfaces</li></ul>	3g
External Bend	<ul style="list-style-type: none"><li>• Neatly finish open ends</li></ul>	3g



# Smooth-Fit Accessories for ½ Circle Trunking

Feature	Comment
Internal shoulders	<ul style="list-style-type: none"> <li>Enables smooth appearance along installation</li> <li>Creates secure fitment - will not drop off</li> <li>Enable smooth flush alignment between lengths for perfect finish</li> </ul>
Abs material	<ul style="list-style-type: none"> <li>Robust material</li> <li>Can be modified for fitment on uneven surfaces</li> </ul>
Can be painted	<ul style="list-style-type: none"> <li>Scuff using gentle abrasive such as fine sandpaper, so paint keys for best results</li> </ul>

Accessory Name	Description		Size	Weight
Internal Bend				
		Join lengths around 90 degree inside corners	16x8mm	1g
			30x15mm	2g
			40x20mm	3g
			50x25mm	7g
			60x30mm	20g
External Bend				
		Join lengths around 90 degree outside corners	16x8mm	1g
			30x15mm	3g
			40x20mm	7g
			50x25mm	14g
			60x30mm	14g
Flat Bend				
		Use between 2 lengths that change direction by 90 degrees on flat surfaces  Requires care in measuring gap required for each Accessory, then cut straight length(s) end so Accessory fits neatly between lengths	16x8mm	1g
			30x15mm	3g
			40x20mm	10g
			50x25mm	14g
			60x30mm	22g
Equal Tee				
		Join 3 lengths of same profile	16x8mm	1g
			30x15mm	4g
			40x20mm	12g
			50x25mm	17g
			60x30mm	23g
Connector				
		Join 2 lengths of same profile on flat surface	16x8mm	1g
			30x15mm	3g
			40x20mm	10g
			50x25mm	14g
			60x30mm	22g
End Cap				
		Neatly finish open ends	16x8mm	1g
			30x15mm	3g
			40x20mm	10g
			50x25mm	14g
			60x30mm	22g

Accessory Name	Description	Size	Weight
<b>Circular Adaptor</b>			
		Connect Mini D-Line to flat edge surface boxes with 20mm diameter 3 circular knock-outs	30x15mm 5g
<b>Patress Adaptor</b>			
		Connect Mini D-Line(interfaces with 30x15mm only) to round Surface Boxes	30x15mm 3g
<b>Cable Inlet/Outlet</b>			
		Takes cables in or out of a 30x15mm installation. Use between lengths on straight runs	30x15mm 2g

### Installation Tips

Plan your cable path. Check that you have all parts required. Next consider the space that will be required for any accessories needed - Smooth-Fit ccessories give a smooth flush-alignment for perfect finish, but require precise measurements and straight cuts. Use the accessory part as a template; pencil mark the surface at the shoulder points of the accessory. These pencil marks indicate the point that the D-Line length needs to measure up to.

example...




- Measure length(s). Pencil mark where cut is required.
- Use a mitre block and junior hacksaw to cut at the outer edge of the pencil mark.
- Remove the protective film cover.
- Peel & stick.. Make sure the surface is clean & dry. Alternatively lengths can be drilled and screw fixed.
- For easier installation we recommend that horizontal runs are fixed with the click lock at the top and the hinge at the base.
- Take care when positioning lengths, as a strong bond will be created with the surface.

### Installing cables & accessories

Lay cables into lengths, place the required accessory over the cables, then close the lid ensuring it snaps shut. The lengths hold the accessories in position.


#### Internal Bend



#### External Bend



#### Flat Bend




#### Equal Tee




#### Cable Inlet/Outlet



#### Connector



#### End Cap



It may be necessary to shape some accessories to allow for imperfections on walls.

### After Care



D-Line can accept gloss or emulsion paints...  
For best results use fine sandpaper to key the surface prior to painting.

**Important:** If using D-Line for 240v mains cables it is recommended you leave 45%+ of internal capacity for air circulation.

# Clip-Over Accessories for ¼ Circle Trunking (22x22mm only)












Feature	Comment
Rear Grip Tabs	<ul style="list-style-type: none"> <li>Hold Accessory in 1mm gap between flat surface and D-Line length as made possible by depth of rear foam-tape</li> </ul>
Abs material	<ul style="list-style-type: none"> <li>Robust material</li> <li>Can be modified for fitment on uneven surfaces</li> </ul>
Can be painted	<ul style="list-style-type: none"> <li>Scuff using gentle abrasive such as fine sandpaper, so paint keys for best results</li> </ul>
Easy-to-install	<ul style="list-style-type: none"> <li>Clip-Over style can forgive poor cuts at length ends, and imprecise measuring so saving installation time</li> </ul>

Accessory Name	Description	Weight
<b>Internal Bend</b>  	<ul style="list-style-type: none"> <li>Join lengths around 90 degree inside corners</li> </ul>	2g
<b>External Bend</b>  	<ul style="list-style-type: none"> <li>Join lengths around 90 degree outside corners</li> </ul>	3g
<b>Cable Inlet/Outlet</b>    	<ul style="list-style-type: none"> <li>Use to provide cable entry/exit point between 2 lengths</li> </ul>	2g
<b>Connector</b>  	<ul style="list-style-type: none"> <li>Joins 2 lengths on flat surfaces</li> </ul>	2g
<b>Internal Bend</b>  	<ul style="list-style-type: none"> <li>Neatly finish open ends</li> <li>Simply push in. (note: left &amp; right versions apply)</li> </ul>	3g



# Smooth-Fit Accessories for ¼ Circle Trunking

Feature	Comment
Internal shoulders	<ul style="list-style-type: none"> <li>• Enables smooth appearance along installation</li> <li>• Creates secure fitment - will not drop off</li> <li>• Enable smooth flush alignment between lengths for perfect finish</li> </ul>
Abs material	<ul style="list-style-type: none"> <li>• Robust material</li> <li>• Can be modified for fitment on uneven surfaces</li> </ul>
Can be painted	<ul style="list-style-type: none"> <li>• Scuff using gentle abrasive such as fine sandpaper, so paint keys for best results</li> </ul>

Accessory Name	Description	Weight
<b>Internal Bend</b>  	<ul style="list-style-type: none"> <li>• Join lengths around 90 degree inside corners</li> </ul>	2g
<b>External Bend</b>  	<ul style="list-style-type: none"> <li>• Join lengths around 90 degree outside corners</li> </ul>	3g
<b>Cable Inlet</b>  	<ul style="list-style-type: none"> <li>• Use to provide cable entry point between 2 lengths</li> </ul>	2g
<b>Cable Outlet</b>  	<ul style="list-style-type: none"> <li>• Use to provide cable exit point between 2 lengths</li> </ul>	2g
<b>Connector</b>  	<ul style="list-style-type: none"> <li>• Joins 2 lengths on flat surfaces</li> </ul>	2g
<b>Internal Bend</b>  	<ul style="list-style-type: none"> <li>• Neatly finish open ends</li> <li>• Simply push in. (note: left &amp; right versions apply)</li> </ul>	3g

## Installation Tips

Plan your cable path. Check that you have all parts required.

Next consider the space that will be required for any accessories needed - Smooth-Fit accessories give a smooth flush-alignment for perfect finish, but require precise measurements and straight cuts.


Use the accessory part as a template; pencil mark the surface at the shoulder points of the accessory.

These pencil marks indicate the point that the D-Line length needs to measure up to.

example...



## Cutting & Installing Lengths



- Measure length(s). Pencil mark where cut is required.
- Use a mitre block and junior hacksaw to cut at the outer edge of the pencil mark.
- Remove the protective film cover.
- To peel & stick... Make sure the surface is clean & dry.
- For easier installation we recommend that horizontal runs are fixed with the click lock at the top and the hinge at the base.
- Take care when positioning lengths, as a strong bond will be created with the surface.

## Installing cables & accessories

Lay cables into lengths, place the required accessory over the cables, then close the lid ensuring it snaps shut. The lengths hold the accessories in position.

### Internal Bend




### External Bend



### Cable Inlet/Outlet



### Connector



### End Cap



## After Care



D-Line can accept gloss or emulsion paints... For best results use fine sandpaper to key the surface prior to painting.



It may be necessary to shape some accessories to allow for imperfections on walls.

**Important:** If using D-Line for 240v mains cables it is recommended you leave 45%+ of internal capacity for air circulation.

## Cable Tidy Units



### LARGE OR SMALL

Cable Tidy Units have been developed in two sizes to hide a 6 way or a 4 way power board, and associated cable clutter. The Units are designed to provide a neat and stylish solution that blends with decor. With all wires and cables neatly concealed, wasted space is returned and surfaces become easier to clean.

A safety trip and spill hazard is also eliminated making this extension block organiser arguably the best around.



### D-LINE CONDUIT COMPATIBLE

The Units have 3 cable exit/entry slots in the rear so a neat appearance is always maintained. If a unit is next to a wall, users can integrate the Cable Tidy Unit with D-Line Cable Trunking by using Trunking lengths to hide entry or exit cables and wires up to a desk or a TV, or along skirting.



### MODERN SAFE SOLUTION

Designed with curved ends and a polished feature on lid, D-Line Cable Tidy Units fit naturally in modern homes and offices and are ideal for hiding cables behind TV's, or from gaming equipment, and on (or below) computer desks... wherever there is cable and wire clutter!

Units are produced from robust ABS material, are recyclable and have been tested and certified to exacting safety standards.