

规格说明书 SPECIFICATION		( AT Ta= 25 Degree.)		
项目/ITEMS	单位/UNIT	参数/PARAMETERS		备注/NOTES
尺寸/Dimension	mm	80*80*15		Length* Width *Thickness
外框/Fan Frame	----	BLACK PBT (UL94V-0)		Glass Fiber Reinforced
扇叶/Fan Impeller	----	BLACK PBT (UL94V-0)		9 Blades
轴承种类/Bearing System	<input type="checkbox"/> S:Sleeve Bearing <input type="checkbox"/> S:Hypro Bearing <input type="checkbox"/> C:CycleSeal Bearing <input checked="" type="checkbox"/> B: Dual Ball Bearing			
额定电压/Rated Voltage	VDC	12.0		N/A
工作电压范围 Operating Voltage Range	VDC	10.8~13.2		N/A
起动电压/Start-up Voltage	VDC	7.0		N/A
额定电流/Rated Current	Amp	0.08(MAX:0.12)		At 25°C/Relative Humidity 65% At rated Voltage, Measured after 3Mins.
标签电流/Label Current	Amp	0.33		N/A
额定功率/Rated Power	Watt	0.96(MAX:1.44)		At 25°C/Relative Humidity 65% At rated Voltage, Measured after 3Mins
额定转速/Rated Speed	RPM	2500±350		At 25°C/Relative Humidity 65% At rated Voltage, Measured after 3Mins
风量/Air Flow	CFM	29.04(MIN:24.98)		Maximum In Free Air, Refer to 4.2.
风压/Air Pressure	mmAq	1.78(MIN:1.31)		Maximum When Air Flow = 0
噪音/Noise Level	dBA	27.5(MAX:30.4)		At Rated Speed, Refer to 4.3.
马达保护/Motor Protection	Polarity Protection	Yes		Refer to 8.1.
锁机保护/Locked Motor Protection	Auto Restart	Yes		Refer to 8.2.
缓启动/Soft Start	----	No		N/A
速度感应/FG Sensor	Tachometer Sensor	Yes		Refer to 2.1.
锁机报警/RD Alarm	Locked Motor Alarm	No		Refer to 2.1.
调速控制/PWM Control	----	No		Refer to 2.2.
防水等级/Waterproof Class	<input type="checkbox"/> IP44 or less	马达三防漆包漆 Motor Coating by Insulating Paint		
	<input type="checkbox"/> IP55/56	纳米真空镀膜 Motor process by NT vacuum coating		
	<input type="checkbox"/> IP67/68	灌胶密封 Motor sealed coating by waterproof Glue		
环保要求/Conform to RoHS	----	Yes		Refer to 6.
安规规格/Safety Approval	----	<input type="checkbox"/> UL <input type="checkbox"/> CUL <input type="checkbox"/> CE <input type="checkbox"/> TUV		
导线/Lead Wire	UL1007/26AWGx300mm	<input checked="" type="checkbox"/> Red(+) <input type="checkbox"/> Black(-) <input type="checkbox"/> Yellow(RD) <input checked="" type="checkbox"/> White(FG) <input checked="" type="checkbox"/> Black(-)		
端子/Connector	----	2510/3P 正向 黑红白 OR Equivalent		Pin1:-, Pin2:+, Pin3:FG
套管/Tube	----	No		----
预估寿命/Life Expectancy	小时/Hours	70000		Refer to 7.
净重/Net Weight	克/Gram	51.10		N/A
装箱/Packing	件/箱/Pieces/Carton	100		N/A