

NOTES:

ELECTRICAL:



1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO+85°
2. OPERATION:0° TO70°

MECHANICAL:

1. HOUSINGG MATERIAL:STAINLESS STEEL
2. INSERT MATERIAL:FAME RETARDANCY PBT
3. PCB MATERIAL:FR-4 T=1.6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE  
STAMP PIN T=0.30mm
5. RJ45 JACK ;IFE:750 TIMES MIN
6. SHIELD MATERIAL: STAINLESS STEEL,  
T=0.2mm

|          |  |              |                        |   |  |   |  |        |              |                              |               |
|----------|--|--------------|------------------------|---|--|---|--|--------|--------------|------------------------------|---------------|
|          |  |              |                        |   |  <b>Wiretek</b> |   |  |        |              |                              |               |
| SYM      |  | Number       | Bill No. of Alteration | Signature   | Date   | Material  |  |        |              | Item No.                     | <b>KJ6-12</b> |
| Drawn    |  | Ding jian bo | 2015.12.29             | Tolerance   |  | Angles Projection   |  | Size   | Scale        | Unit                         | Part Name     |
| Checked  |  | Ge pei jun   | 2015.12.29             | $0.00-20.00$ $\pm 0.10$<br>$20.00-50.00$ $\pm 0.15$<br>$50.00-100.00$ $\pm 0.20$<br>$100.00-$ $\pm 0.25$<br><i>Angle</i> $\pm 30^\circ$ |  |  |  | A4     | X:1          | mm                           | ERP           |
| Approved |  | Wang wei jun | 2015.12.29             |   |  | Sheet   |  | 1 OF 1 | Version: A/0 |                              | Part No.      |
|          |  |              |                        |   |  |   |  |        |              | STP Cat.6 coupler, RJ45-RJ45 |               |