

20W Premium Adjustable LED Downlight

Model: LEDDL20WXKR



The ENSA™ premium adjustable downlight range provides a versatile series of LED downlights for general purpose illumination in retail, residential or office environments. They are ideal for efficient tailored lighting applications, such as spot and feature lighting.


- High efficiency, low energy use 20W LED downlight.
- Versatile housing with 350° rotate / 60° vertical tilt adjust.
- Excellent colour rendering, lifespan and light output.
- Superior build quality and thermal management.
- Cool white and warm white colour temperatures.
- Completely frosted diffuser to eliminate LED glare.

Light Specifications

| | | |
|------------|------------------------|-------------------------------|
| Optical | Luminous Flux | 1700lm |
| | Luminous Efficiency | 85lm/W |
| | Colour Temperature | 3000K / 6500K |
| | Colour Rendering Index | >80 |
| | Beam Angle | 60° |
| | Light Decay | 30% over 25,000 hours |
| | Rated Lifespan | >50,000 hours |
| Electrical | LED Power Consumption | 20W |
| | Input Voltage | 85 ~ 265VAC |
| | Power Factor | >0.9 |
| | Dimmable | No |
| General | Plug / Socket / Base | Transformer included; no plug |
| | Reflector / Diffuser | Frosted Diffuser |
| | Housing Adjustments | Tilt 60° / Rotate 350° |
| | Operating Environment | -20°C ~ 40°C |
| | Dimensions | Ø195 x 175mm |
| | Hole Cut Size | Ø165mm |
| | Equivalent Wattage | 70W |

Photometric Diagrams

The photometric results shown below are a result of testing the cool white variant of this downlight at 60° beam angle.



Your local ENSA™ LED lighting professional: