

WES AUSTRALASIA

Product Code: MSPT10

DATA SHEET



Feature:

- Mains surge LED indicator.
- Gas tube arrestor for telecom protection.
- 3 x M.O.V for Mains protections.
- Slimline design (fit two side by side in dual power point).
- Fully Approved with insulated plug pins
- 2x Standard RJ12 socket telephone connection.

Mains Specifications		Telecom. Specifications	
Load Rating:	240Vac 50Hz, 10A	DC Break Down Voltage:	460V
Max Clamping Voltage:	710V (8/20 μ S)	Surge Break Down:	< 800V
Max Peak Current:	4500A (8/20 μ S)	Surge Discharge Current:	10 kA (8/20 μ S)
Max Energy:	146J (10/1000 μ S)	AC Discharge Current:	10 A
Response Time:	Less than 1 nS (10/1000 μ S)	Insulation Resistance:	> 10 G Ω (@100V)
Protection Modes: Active-Neutral, Active-Earth, Neutral-Earth		Protection Modes: Tip – Earth & Ring – Earth	

Compliance

Mains:
AS/NZS-3197, AS/NZS-3100, AS/NZS-3112.

Telecommunication:
TS001, AS/NZS 3260, AS/NZS: 4117, AS/NZS 4251.1

