

LN-A37 Large Alligator Clip

Specifications

- * Rating : CATIII 1000V CATIV 600V
- * Current : 20A
- * Colour : Black, Red
- * Connection : Slide-on 2mm Jack With No.4 (T=48) screw
Option : **4mm Jack (LN-A35)**
- * Jaw Opening : 34mm
- * Recommended for use with LN-S05 test leads



LN-A41 Alligator Clip Test Lead (Right Angle)

Specifications

- * Rating : CATIII 1000V CATIV 600V
- * Current : 10A
- * Colour : Black, Red
- * Connection : 4mm Banana Plug
Option : **Straight (LN-A43)**
- * Lead Length : 750mm
- * Lead Type : UL1803 PVC (Dual-layer insulation)



LN-S09 Detachable Test Lead Set (Right Angle)

Specifications

- * Rating : CATIII 1000V CATIV 600V
- * Current : 10A
- * Colour : Black, Red
- * Connection : 4mm Banana Plug
Option : **Straight (LN-S11)**
- * Test Probe : 2mm
- * Lead Length : 900mm
- * Lead Type : UL1803 PVC (Dual-layer insulation)



LN-N02 Flexible 0.75mm Test Probe

Specifications

- * Colour : Black, Red
- * Connection : 2mm Jack
- * Length : 30mm
- * Test probe : 0.75mm Gold-plated Flexible
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe Test Lead.



LN-N13 Mini Test Hook Clip

Specifications

- * IEC Rating : CATII 300V
- * Current : 2A
- * Colour : Black, Red
- * Connection : 2mm Jack
- * Clip Type : Mini test clip (41mm).
- * Lead Length : 155mm
- * Lead Type : UL1007PVC With Braided.
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe.



LN-N19 Little Alligator Clip

Specifications

- * IEC Rating : CATII 300V
- * Current : 2A
- * Colour : Black, Red
- * Connection : 2mm Jack
- * Clip Type : Mini test clip
- * Lead Length : 135mm
- * Lead Type : UL1007PVC With Braided
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe Test Lead.



LN-A40 Little Alligator Clip

Specifications

- * Rating : CATIII 1000V CATIV600V
- * Current : 10A
- * Colour : Black, Red
- * Jaw Opening : 8.5mm
- * Connection : Slide-on 2mm Jack With No.4 (T=48) screw
Option : **4mm Jack (LN-A38)**
- * Recommended for use with LN-S05 test leads



LN-S05 Safety Test Lead Set (Right Angle)

Specifications

- * Rating : CATIII 1000V CATIV 600V
- * Current : 10A
- * Colour : Black, Red
- * Connection : 4mm Banana Plug
Option : **Straight (LN-S07)**
- * Lead Length : 900mm
- * Test Probe : 2mm with No.4(T=48)Screw
- * Lead Type : UL1803 PVC (Dual-layer insulation)



LN-N01 K-type Thermocouple Adapter

Specifications

- * Adapts K-Type thermocouple mini-connector to dual shrouded banana plug inputs
- * Measurement range and accuracy: probe dependent
- * Suitable for low voltage applications (below 30 V AC, 60 V DC)
- * Size : 51x37x14.5mm



LN-N07 1mm Test Probe

Specifications

- * IEC Rating : CATIII 1000V
- * Current : 2A
- * Colour : Black, Red
- * Connection : 2mm Jack
- * Shaft Length : 58mm
- * Test probe : 1mm stainless
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe Test Lead.



LN-N14 Micro Test Hook Clip

Specifications

- * IEC Rating : CATII 300V
- * Current : 2A
- * Colour : Black, Red
- * Connection : 2mm Jack
- * Clip Type : Micro test clip (57mm)
- * Lead Length : 155mm
- * Lead Type : UL1007 PVC With Braided
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe.



LN-N46 Flat Alligator Clip

Specifications

- * IEC Rating : CATII 300V
- * Current : 2A
- * Colour : Black, Red
- * Connection : 2mm Jack
- * Clip Type : Flat alligator clip
- * Lead Length : 135mm
- * Lead Type : UL1007 PVC With Braided
- * The 2mm Jack design allows quick and easy connection to any 2mm Probe Test Lead.

