

## Commercial LED High Bay Lighting




LHB-D Series: Commercial hanging/bracket mount high bay lighting in 150W

The ENSA™ LHB-D high bay series delivers energy efficient lighting to industrial and commercial environments at an economic price point. They are also weather-resistant, making them ideal for outdoors installations and events.

The LHB-D series delivers ideal lighting conditions in areas with high ceilings up to 12m, such as warehouses, manufacturing facilities and exhibition halls, with a high luminous efficacy for optimal power consumption. Each light has a compact, robust aluminium body and comes in 5700K cool white colour temperature.

- 150W industry-ready LED high bay
- High 130lm/W luminous efficacy for energy efficiency
- Hanging and adjustable bracket mounting options
- Compact and robust: no additional reflector required
- Efficient heatsink cooling technology, IP66 weather rated
- Available in 5700K cool white with 120° beam angle

## Series Specifications

Model	LHB-D150
Product Image	
Series Name	LHB-D Series: Commercial LED High Bay Series
<b>Optical</b>	
Light Output	19500lm
Luminous Efficacy	130lm/W
Colour Temperature	5700K
Colour Rendering Index	>80
Beam Angle	90°
Rated Lifespan	50,000 hours
<b>Electrical</b>	
Power Consumption	150W
Input Voltage	100~277VAC
Power Factor	> 0.93
Dimmable	N/A
<b>General</b>	
Ingress Protection	IP66
Plug / Socket / Base	3-pin AC plug
Reflector / Diffuser	Aluminium / Polycarbonate
Housing Adjustments	180° adjustable housing (bracket mount)
Operating Environment	-20 ~ 40°C
Dimensions	Ø330 x 155mm
<b>Photometry</b>	
Illuminance at a Distance	
Luminous Light Distribution	

## Ordering Information

Type	Series	Wattage	Colour Temperature		
LHB	-	D	150 (150W)	-	C (Cool white)
LHB-D150-C: 150W LED High Bay in Cool White					