

LP45F700MINI

UHF Aerials

Log-periodic MINI pre-assembled aerials for UHF band characterized by extremely easy connection due to the F connector being located near the mast clamp.

Technical Chars

- Thanks to the special pole mount, the antenna can be installed in both vertical and horizontal **polarisation without adapters** or other accessories.
- The geometric distribution of the dipoles has been redesigned to achieve excellent filtering for interfering signals in the 5G and 4G LTE band above 694 MHz reserved for mobile telephony.
- It features excellent mechanical resistance for fixing the elements to the cradle, excellent mechanical resistance to rotation on the pole, and good electrical performance.
- The F connector is protected by a bayonet connector cover.
- Black colour antenna.

| LP45F700MINI | | |
|---|--------|---------------|
| Code | | 216256 |
| Elements | n° | 10+10 |
| Band | | UHF |
| Channel | | E21-E48 |
| Bandwidth | MHz | 470-694 |
| Gain | dBi | 9 |
| Front/Back ratio | dB | 30 |
| Return loss | dB | -15 |
| Beam width (3dB) | 0 | ±30 |
| Wind load 120Km/h 729N/m² | Kg (N) | 2.7 (26.5) |
| Connector | | F |
| Impedence | Ohm | 75 |
| Max mast diameter | mm | 60 |
| Dimensions | cm | 44 x 36 |
| Accessories | | |
| Horizontal polarization | | Included |
| Horizontal polarization Tilt adjustment | | PV10 (210011) |
| Vertical polarization | | Included |
| Vertical polarization Tilt adjustment | | PV10 (210011) |
| Auxiliary boom | | N.P. |
| Dimensions and packaging | | |
| Pcs | | 30 |
| EAN code | | 8016978104093 |
| Multiple EAN | | 8016978104277 |