

Preliminary

RL50AWC2E-005 LED12V-CW

DATA SHEET



QC:楊艷玲

ENG:李冰紅

Prepared By:陳結佩


Part No.	RL50AWC2E-005	Spec No.	S/N-21091602	Page	1 of 4
----------	---------------	----------	--------------	------	--------

Version:1.0

Features:

- ◆ High intensity
- ◆ 5mm diameter package
- ◆ General purpose leads
- ◆ Pb-free

Package Dimensions:



Part NO.	Chip Material	Lens Color	Emission Color
RL50AWC2E-005	InGaN	Water Clear	Super Bright White

Notes:

1. All dimensions are in millimeters (inches).
2. Tolerance is $\pm 0.25\text{mm}$ (.010") unless otherwise noted.
3. Protruded resin under flange is 1.0mm (.04") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.
6. Precautions for ESD:
Static electricity and surges can damage the LED. It is recommended to use an anti-electrostatic wrist band or glove when handling the LED. All devices, equipment and machinery must be properly grounded.
7. This data-sheet only valid for six months.

Absolute Maximum Ratings at Ta=25°C

Parameter	MAX.	Unit
Power Dissipation	156	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	12	mA
Derating Linear From 50°C	0.4	mA/°C
Reverse Voltage	5	V
Electrostatic Discharge (ESD)	2000	V
Operating Temperature Range	-20°C to +80°C	
Storage Temperature Range	-30°C to +100°C	
Lead Soldering Temperature [4mm(.157") From Body]	255±5°C for 5 Seconds	
Wave Soldering Temperature	Peak Temperature 245°C~260°C for 10 Seconds	

Electrical Optical Characteristics at Ta=25°C

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I _V	13000	30000		mcd	I _F =10mA (Note 1)
Viewing Angle	2θ _{1/2}	10	15	20	Deg	(Note 2)
Forward Voltage	V _F		11	13	V	I _F =10mA
Reverse Current	I _R			10	μA	V _R =5V



Color Rank	x	y	x	y	x	y	x	y
BIN 1D	0.453	0.4355	0.4698	0.4399	0.4835	0.4655	0.4658	0.4615
BIN 1A	0.4378	0.4039	0.4525	0.408	0.4698	0.4399	0.453	0.4355
BIN 2D	0.438	0.4312	0.453	0.4355	0.4658	0.4615	0.4495	0.4575
BIN 2A	0.4242	0.399	0.4378	0.4039	0.453	0.4355	0.438	0.4312
BIN 3D	0.4245	0.4263	0.438	0.4312	0.4495	0.4575	0.434	0.452
BIN 3A	0.4116	0.3938	0.4242	0.399	0.438	0.4312	0.4245	0.4263
BIN 4D	0.4112	0.4196	0.4245	0.4263	0.434	0.452	0.4205	0.447
BIN 4A	0.4006	0.3885	0.4116	0.3938	0.4245	0.4263	0.4112	0.4196

Notes:


1. Luminous intensity is measured with a light sensor and filter combination that approximates the CIE eye-response curve.
2. θ_{1/2} is the off-axis angle at which the luminous intensity is half the axial luminous intensity.
3. Forward voltage measurement allowance is ±0.1V
4. Luminous Intensity Measurement Allowance is ±10%

Typical Electrical / Optical Characteristics Curves **(25°C Ambient Temperature Unless Otherwise Noted)**


CIE 1931 Chromaticity Diagram




Relative Luminous Intensity vs Forward Current




Forward Current vs Forward Voltage



Forward Current VS. Chromaticity coordinate



Forward Current Derating Curve



Beam Pattern

