



ANC-4150 Version: 1

## 5m Antenna Cable, CFD-400, N Male Plug to N Male Plug, Indoor/Outdoor

LevelOne provides a higher performance CFD 400 cable with excellent flexibility. All cables designed for low loss general-purpose indoor/outdoor applications. Weatherability CFD 400 cables designed for outdoor exposure incorporate the best materials for UV resistance.

### Key Features

- Compatible with IEEE 802.11a/b/g/n/ac wireless standards
- N male to N male
- Heat shrink tubing on both ends for wire insulation and protection
- CFD-400 low loss coaxial cable

### Specifications

#### System Specifications

**Standards & Protocols:**

CFD 400

**Connector:**

N male to N male

**Impedance (Ohms):**

50 $\pm$  5?

**VSWR:**

1000~2000MHZ ?1.2

3000~6000MHZ ?1.5

**Capacitance:**

23.9 PF/FT

**Conductor Material:**

Copper Clad Aluminum

**Conductor Size:**

2.74 mm

**Conductor Resistance (?/Km):**

1.67?

**Insulation Thickness:**

2.2mm



**Insulation Material:**

PFE

**Insulation O.D:**

7.24mm

**Jacket Material:**

PVC or PE

**Jacket O.D:**

10.3 ± 0.25 mm

**Binder:**

Sealed aluminum mylar tape

## Wireless

**Frequency Band:**

0~6GHz

## Features

**General:**

Low-loss cable assemblies

## Performance

**Cable Loss:**

<-2.0 dBi

**Attenuation:**

30 MHz: 0.8 dB/100 ft

50 MHz: 1 dB/100 ft

150 MHz: 1.7 dB/100 ft

220 MHz: 2.1 dB/100 ft

450 MHz: 3.1 dB/100 ft

900 MHz: 4.7 dB/100 ft

1500 MHz: 6.1 dB/100 ft

2000 MHz: 7.2 dB/100 ft

## Environment

**Temperature (°C):**

-30? ~ +60?

**Humidity (Non-condensing):**

95% @ 55°C

**Installation:**

Indoor/Outdoor

## Physical Specifications

**Diameter:**

235\*235\*50 mm

**Weight (g):**

590 g


**Color:**

Black

Length:  
5m

---

## Diagram



---

## Order Information

ANC-4150

---

## Package Contents

ANC-4150

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.