



FCS-1041 Version: 1

PTZ Network Camera, 2-Megapixel, 802.3af PoE, WDR, 10x Optical Zoom



1. Status LEDs
2. Microphone
3. Ethernet
4. DI/DO



5. Line Output
6. SD/SDHC Card Slot
7. Mic/line Input

8. DC Power Jack
9. Reset Button
10. USB Port

Key Features

- Support unique features for auto-tracking function of moving objects
- 2-Megapixel (1920 x 1080) high-definition resolution
- Supports 355° pan and 135° tilt
- Supports 10x optical zoom
- Supports 2 video streams simultaneously
- Compression: H.264/MPEG-4/MJPEG
- Built-in microphone and external speaker for 2-way audio communication
- Built-in SD/SDHC card slot for local storage
- Digital input/output (1DI/1DO) for sensor and alarm
- Supports motion detection and event notification via e-mail or FTP
- Free video surveillance and CMS (Central Management System) software with 64-channel license



Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3af Power over Ethernet (PoE)
TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, NTP, PPPoE, DNS, DHCP, RTSP, Samba

Image Sensor:

2-Megapixel 1/2.7" Progressive Scan CMOS

Connectors and Cabling:

1 x RJ-45 10/100/1000 Mbps PoE port
1 x 3.5mm line out
1 x 3.5mm mic/line in
1 x USB port (for optional USB flash drive)
1 x DC Power Jack
I/O terminal block (1 DI/1 DO)

Modularity:

1 x SD/SDHC card slot

Button:

Reset Button

Indicator:

Power, Link

Lens:

Zoom, Auto iris, Auto-focus, f=4.9-49mm, F1.8-3.0

Shutter Time:

1 ~ 1/10,000 sec.

Angle of View:

66.6°

Pan/Tilt/Zoom:

Pan range: $\pm 355^\circ$ (-177.5°~177.5°)
Tilt range: $\pm 135^\circ$ (-45°~ 90°)
10x Optical Zoom
4x Digital Zoom
Auto pan mode
Auto patrol mode

Video Compression:

H.264 / MPEG4 / MJPEG

Resolution:

2M (1920x1080)

Video Format:

MPEG4

Audio Compression:

G.711 / AMR

Power:

Power Consumption: 8 W
Power Input: DC12V 1.5A / 802.3af PoE

Features

General:

Backup: SD/SDHC card slot & USB port for local storage
DNS: Easy Internet monitoring via configuration free Level1DNS™ service

Security:

Alarm and Notification: Alarm: Motion Detection; DI/DO
Notification: FTP, SMTP, Samba
Access Control: Multi-level user access with password protection
IP address filtering
HTTPS encrypted data transmission

Video:

Image Setting: - Adjustable image size, quality and bit rate
- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Wide Dynamic Range (WDR)
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Time Stamp
Streaming: Up to 2 video streams
Motion Detection: 16 Detection Zones

Audio:

Streaming: 2-way audio
Input/Output: Built-in microphone
Mic/line input, line output

Performance**Number of Clients:**

20

Data Transfer Rate:

10/100/1000Mbps

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Frame Rate:

Up to 30 fps at 1920x1080

Minimum illumination:

Color: 1.5 lux at F2.0

B/W: 1.0 lux at F2.0

Environment**Temperature (°C):**

Operating: 0°C ~ 40°C

Humidity (Non-condensing):

Operating: 10% ~ 85%

Physical Specifications**Dimensions (W x D x H mm):**

107 x 105 x 110 mm

Weight (g):

425 g

Others



Approval and Compliance:

CE, RoHS, FCC, ONVIF

Deployment:

Desktop/Ceiling Mount

Operation Systems:

Microsoft Windows 8/7/Vista/XP

Viewing Systems:


Browser: Internet Explorer 6.x or above, Firefox, Chrome, Safari

Cell phone: 3GPP player

Real Player: 10.5 or above

Quick Time 6.5 or above"

Diagram



Order Information

FCS-1041

Package Contents

FCS-1041

Power Adapter

Mounting Kit

Screw Kit

RJ45 Network Cable

Quick Installation Guide

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.