





FCS-1152 Version: 1

- ! Mounting kits are to be ordered separately.
- ! Power supply unit is to be ordered separately.

Fixed IP Network Camera, 5-Megapixel, 802.3af PoE



1. Ethernet Port
2. Memory Card Slot
3. Power LED
4. Reset Button
5. Audio Input/ Output & Digital Input/ Output



6. Monitor Distance Adjustment
7. Focal Length Adjustment
8. DC Iris Port

Key Features

- Built-in Micro SDHC/SDXC card slot for local storage
- 5-Megapixel high-definition resolution
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Video compression: H.264/MJPEG
- Removable IR-cut filter for day and night surveillance
- Power support: PoE (IEEE 802.3af)
- Free surveillance and CMS (Central Management System) software packages with 64-channel license



Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T, Ethernet
IEEE 802.3u 100-BASE-TX, Fast Ethernet
IEEE 802.3af Power over Ethernet (PoE)
TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour

Image Sensor:

5-Megapixel 1/3.2" Progressive Scan CMOS

Lens:

Vari-focal, DC iris, Manual focus, f2.8-12mm, F1.4

Port:

1 x RJ-45 10/100 Mbps PoE Port
1 x Auto Iris (DC Drive)
I/O terminal block (1 DI/1 DO)
1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

Shutter Time:

1/5 ~ 1/10,000 sec

Angle of View:

70.9° - 29.2°

Pan/Tilt/Zoom:

Digital Zoom to very high detail available on Software

Video Compression:

H.264 / MJPEG

Resolution:

5M (2592x1944)

Video Format:

RAW

Audio Compression:

G.711

Power Input:

802.3af PoE

Power Consumption:

PoE Class 2 (IEEE802.3af) / 4.002W

Data Transfer Rate:

10/100Mbps

Features

General:

Backup: MicroSDHC /MicroSDXC card slot for local storage

Video:

Image Setting: - Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- AGC/AWB/AES

- Back Light Compensation (BLC)

- Wide Dynamic Range (WDR), Basic WDR (74 dB)

- 2D Noise Reduction (2DNR)

Streaming: Up to 2 video streams

Performance

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Frame Rate (fps):

15fps at 2592 x 1944; 15 fps at 2048x1536; 30 fps at 1920 x 1080; 30 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.1 lux at F1.4

B/W: 0.05 lux at F1.4

Environment

Temperature (°C):

Operating: -10°C ~ 50°C

Humidity (Non-condensing):

Operating: 10% ~ 85%

Installation:

Wall Mount

Physical Specifications

Dimensions (W x D x H mm):

67 x 169 x 65 mm

Weight (g):

438 g

Approval and Compliance

EMI/EMS:

CE, RoHS, FCC, ONVIF


Others

Operation Systems:

Microsoft Windows 8/7/Vista/XP



Diagram



Order Information

FCS-1152

Package Contents

FCS-1152
Screw Kit
Quick Installation Guide
Resource CD (User Manual, QIG)

Optional Accessory



CAS-3104
Wall Mount Bracket



CAS-3105
Bracket for Zoom Box Cameras

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.