

FCS-3401 Version: 1

GEMINI Fixed Dome IP Network Camera, 2-Megapixel, H.265, Vandalproof, 802.3af PoE, Indoor/Outdoor

The LevelOne FCS-3401 is a fixed-position outdoor camera offering an ultra-reliable, cost-effective solution for outdoor IP surveillance networks, and is rated at IP67 to operate within rain, extreme heat, snow, dust and humid conditions. Offering clear, sharp imagery with 2-Megapixel resolution and the versatility of 802.3af standard PoE to transfer power and data via a single Cat.5 cable, the LevelOne FCS-FCS-3401 Should be an essential part of any security deployment that requires smart, reliable outdoor cameras.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, H.265, MJPEG
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Supports IPv4/IPv6 network operation
- Vandal-proof IK08-rated housing
- Weatherproof IP66-rated housing
- Built-in Micro SD/SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards:

TCP/IP (IPv4/v6), UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, Bonjour, IEEE802.1x

Image Sensor:

1/2.7" Progressive Scan CMOS

Lens:

2.8mm, F2.0

Port:

10/100Mbps (100Base-T) RJ45 Ethernet interface Power Connector

1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset Button

www.level1.com Page 1 of 4

Indicator:

Power

IR LED:

Up to 10 m

Angle of View:

114°

Video Compression:

H.265/H.264 /MJPEG

Resolution:

50Hz:25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Output Video Format:

AVI

Power Input:

12 VDC, 0.7 A, max. 8.5W, ? 5.5mm coaxial plug power PoE (802.3af, 36V to 57V), 0.3 A to 0.1 A, max. 10W

Power Consumption:

8.5W

Data Rate:

256 Kbps to 16 Mbps

Storage Capacity:

Built-in Micro SD/SDHC/SDXC slot, up to 128G

Digital Zoom:

8x Zoom

Features

General:

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser, Third Stream Server

PoE:

(802.3af, class 3)

Security:

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

Management:

Face Detection

Region of Interest: Support 1 fixed region for main stream and sub-stream separately

Video:

Adjustable image size, quality and bit rate

- Configurable brightness, sharpness, contrast, saturation, white balance and exposure
- AGC/AWB/AES
- Back Light Compensation (BLC)
- Wide Dynamic Range (WDR) 120dB
- 3D Noise Reduction (3DNR)
- Flip & Mirror
- Rotate Mode
- Portrait Mode
- Privacy Mask
- Automatic Day/Night
- ICR

www.level1.com Page 2 of 4

Performance

Number of Clients:

Up to 32 users

3 levels:Administrator,Operator,User

Frame Rate (fps):

Main Stream

50Hz:25fps (1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 960, 1280 × 720)

Sub Stream

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream

 $50 \text{Hz: } 25 \text{fps (} 1920 \times 1080, \, 1280 \times 720, \, 640 \times 360, \, 352 \times 288) \, \, 60 \text{Hz:} 30 \text{fps (} 1920 \times 1080, \, 1280 \times 720, \, 640 \times 1080, \, 1280 \times 10$

 \times 360, 352 \times 240)

Minimum illumination:

Color: 0.01 Lux @ (F1.2, AGC ON), 0.028 lux @(F2.0, AGC ON), 0 lux with IR

Environment

Operating Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F),

Operating Humidity (Non-condensing):

Humidity 95% or less (non-condensing)

Installation:

Junction Box

Physical Specifications

Dimensions (W x D x H mm):

110 x 110 mm × 56.4 mm (4.3" x 4.3" × 2.2")

Weight (g):

400g

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Others:

Onvif

Others

Supported Browsers:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Order Information

FCS-3401

Package Contents

FCS-3401 Screw Kit

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Optional Accessory



CAS-7310
Junction box for Dome Camera

www.level1.com Page 4 of 4