



FCS-4047 Version: 1

## PTZ IP Network Camera, 4-Megapixel, IR LEDs, 30X Optical Zoom, Indoor/Outdoor

The LevelOne FCS-4047 is a PTZ IP surveillance camera designed for use outdoors, boasting 4-Megapixel resolution and a 30X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

### Key Features

- 4-Megapixel high-definition resolution
- Video compression: H.264/MJPEG
- Supports 30X optical zoom
- Built-in infrared LEDs for night viewing up to 150m
- Weatherproof IP66-rated housing
- Triple power support: 12V DC/24V AC/PoE (IEEE 802.3at 60W)
- 90° pan and 60° tilt movements allow for a wide range of monitoring angles

### Specifications

#### System Specifications

##### Standards & Protocols:

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, ARP

##### Image Sensor:

1/2.8" Sony Progressive CMOS

##### Lens:

4.3-129 mm

1m (Wide) ; 1.2m (tele)

F 1.6 (Wide); F 4.7 (Tele)

##### Port:

DC Jack

Audio

10/100/1000 Mbps Ultra PoE

Di/DO

RS-485

BNC

**Button/Knob:**

Reset

**Indicator:**

Power

**IR Cut Filter:**

Yes

**IR LED:**

150 Meter

**Shutter Time:**

1/1 ~ 1/10000 sec

**Angle of View:**

360° endless

**Pan/Tilt/Zoom:**

Pan speed 0.1° ~ 90°/s

Tilt speed 0.1° ~ 60°/s

Preset point speed 9° ~ 280°/s

Preset point speed 7° ~ 300°/s

**Video Compression:**

MJPEG / H.264 (MPEG-4 Part 10/AVC) Baseline / Main Profile / High Profile

**Resolution:**

4-MP (2688x1512 or 2560x1440)

**Video Format:**

AVI

**Audio Compression:**

G.711 / G.726 / AAC

**Power Input:**

Ultra PoE injector(POI-5001) 60W/ AC 24V  $\pm$  20% / DC 12V

**Power Consumption:**

43W (with IR & Heater on)

## Features

**PoE:**

Ultra PoE injector(POI-5001) 60W/ AC 24V  $\pm$  20% / DC 12V

**Security:**

User and Administrator

**Video:**

Auto Flip

Motion Detection on Window x 4 sets

Privacy Mask Max 20 Mask

## Performance

**Number of Clients:**

16

**Storage Capacity:**

SD card Support Max 64Gb

**Frame Rate (fps):**

H.264 4-MP (2560x1440) @25/30 fps

## Environment

Temperature (°C):

-40°C ~ 50°C (-40°F ~ 122°F)

Humidity (Non-condensing):

10% ~ 90%

## Physical Specifications

Dimensions (W x D x H mm):

ø207.43 x 300.39 mm w/ Sunshield

Weight (g):

3.8 kg

Color:

White

## Approval and Compliance

EMI/EMS:

CF/FCC

Environmental Test:

IP66

Others:

ONVIF

## Others

Viewing Systems:

Internet Explore (10.0+) / Firefox / Safari

---

## Order Information

FCS-4047

---

## Package Contents

FCS-4047

Resource CD (User Manual, Utility)

Power Adapter

Mounting Kit



## Optional Accessory



### **CAS-3261**

Pole Thin Direct Mount Kit

No liability or responsibility for any errors or omissions in the content.  
Specifications are subject to change without notice.  
All mentioned brand names are registered trademarks and property of their owners.  
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.