



FCS-4048 Version: 1

! Mounting kits are to be ordered separately.

PTZ IP Network Camera, 2-Megapixel, IR LEDs, Indoor/Outdoor, 33X Optical Zoom

The LevelOne FCS-4048 is a PTZ IP surveillance camera designed for use outdoors, boasting 2-Megapixel resolution and a 33 X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264/MJPEG
- Supports 33X optical zoom
- Built-in infrared LEDs for night viewing up to 150m
- Weatherproof IP66-rated housing
- Vandal-proof IK10-rated housing
- 360° pan and 220° tilt movements allow for a wide range of monitoring angles
- Triple power support: 12V DC/24V AC/PoE (IEEE 802.3at 60W)

Specifications

System Specifications

Standards & Protocols:

TCP, UDP, HTTP, HTTPS, DHCP, PPPoE, RTP, RTSP, IPv4, IPv6, DNS, DDNS, NTP, ICMP, ARP, IGMP, SMTP, FTP, UPnP, SNMP, Bonjour, 802.1x

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

f4.5 - 148.5mm / F1.6 - 5.0

Port:

1 x RJ-45 10/100 Mbps PoE plus port

1 x Line In

1 x Line Out

1 x Power terminal block

I/O terminal block (4 DI/2 DO)

1 x MicroSDHC/ MicroSDXC card slot

Button/Knob:

Reset

Indicator:

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

150 Meter

Shutter Time:

1/5 - 1/32,000 sec (manual mode); 1/5 - 1/32,000 sec (auto mode)

Angle of View:

Horizontal Viewing Angle 69.3° - 3°

Pan/Tilt/Zoom:

Preset Panning / Tilting Speed: 0.16° ~ 300°/s / 0.16° ~ 150°/s

Manual Panning / Tilting Speed: 0.16° ~ 54.4°/s / 0.16° ~ 27.2°/s

Scan Panning / Tilting Speed: 0.16° ~ 32°/s / 0.16° ~ 16°/s

Panning Range :360° Endless

Tilting Range: -20° ~ 200°

33X zoom optical

Remote manual control; 256 preset points;10 preset tours; Auto scan

Video Compression:

RAW

Resolution:

60 fps at 1920 x 1080; 60 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Video Format:

H.264/ MJPEG

Audio Compression:

8 kHz, Mono, PCM, 16 bit encoding; G.711

Power Input:

High PoE (IEEE802.3at 50W) / AC 24V

Power Consumption:

25W, Standard without FAN/Heater

50W, without heater

62W, With heater and fan (by 24V AC only)

Data Transfer Rate:

128 Kbps - 12 Mbps (per stream)

Features

General:

Video motion detection (10 regions); External device through digital input; Sound detection

PoE:

High PoE (IEEE802.3at)

Security:

IP address HTTPS encryption; Password protected user level; Anonymous login; IEEE 802.1X network access control

Management:

Notify control center; Go to PTZ preset point or preset tour; Change camera settings; Command other devices;E-mail with snapshots;

Save video or snapshot to local storage; Upload video or snapshot to FTP server; Activate external device through digital output

Video:

Extreme WDR (145 dB), 2 video stream, Privacy Mask

Audio:

8 kHz, Mono, PCM, 16 bit encoding; G.711

Cable with 3.5mm phone jack

Performance

Number of Clients:

16

Storage Capacity:

SD/MicroSD memory card of up to 64GB

Frame Rate (fps):

60 fps at 1920 x 1080; 60 fps at 1280 x 720; 30 fps at 640 x 480; 15 fps at 320 x 240

Minimum illumination:

Color: 0.05 lux at F1.6 (30 IRE, 2400°K); B/W: 0 lux at F1.6 (30 IRE, 2400°K)

Environment

Temperature (°C):

-40°C ~ 50°C (-40°F ~ 122°F) within 30mins

Humidity (Non-condensing):

10% ~ 85% RH

Physical Specifications

Dimensions (W x D x H mm):

170 mm x 260 mm (6.69" x 10.23")

Weight (g):

3450

Color:

White

Approval and Compliance

EMI/EMS:

CF/FCC

Safety:

IK10

Environmental Test:

IP66

Others:

Manufactured in ISO-9001 and ISO-14001 certified factory

ONVIF

Others

Viewing Systems:

Microsoft Windows 8/7/Vista/XP/10

Compatibility:

Microsoft Internet Explorer 11



Order Information

FCS-4048

Package Contents

FCS-4048

Power Terminal Block

Power adapter with power cord

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.