



FCS-4059 Version: 1

PTZ IP Network Camera, 3-Megapixel, H.265, 30X Optical Zoom, IR LEDs, Indoor/Outdoor

The LevelOne FCS-4059 is a PTZ IP surveillance camera designed for use outdoors, boasting 3-Megapixel resolution and a 30X optical zoom. The camera features motorized Pan and Tilt features as well, enabling it to focus in a variety of directions and zoom in on a specific viewing area. The camera is also PoE, enabling it to run both power and data on the one Cat.5 cable, making deployments easy and efficient. An IP66-rated weatherproof casing allows for safe, reliable operation in outdoor conditions such as rain, heat, dust, snow and humidity.

Key Features

- 3-Megapixel high-definition resolution
 - Video compression: H.264, H.265, MJPEG
 - Supports 30X optical zoom
 - Built-in infrared LEDs for night viewing up to 200m
 - Weatherproof IP66-rated housing
 - Triple power support: 12V DC/24V AC/PoE (IEEE 802.3at 60W)
 - 90° pan and 60° tilt movements allow for a wide range of monitoring angles
-

Specifications

System Specifications

Standards & Protocols:

IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, ARP

Image Sensor:

Sony 1/2.8" Sony Progressive CMOS

Lens:

focus, zoom, P-Iris, Auto-Iris, F1.6, 4.3-129 mm

Port:

10/100/1000 Mbps Ultra PoE
Audio in /out (Terminal Block)
DI x 4 /DO x2 (Terminal Block)
RS-485(Terminal Block)
DC12V (Terminal Block)
AC24V (Terminal Block)
BNC (CVBS Connector)
DC Jack

**Button/Knob:**

Reset

Indicator:

Power

IR Cut Filter:

Yes

IR LED:

200 Meter

Shutter Time:

1/1 ~ 1/10000 sec

Angle of View:

360° endless,62° (wide),2° (tele)

47° (wide),2° (tele)

Pan/Tilt/Zoom:

Pan speed 0.1° ~ 90°/s

Tilt speed 0.1° ~ 55°/s

Preset point speed 9° ~ 280°/s

Preset point speed 7° ~ 280°/s

Video Compression:

H.264/ H.265 / MJPEG

Resolution:

3-MP (2065x1553)

Output Video Format:

AVI

Audio Compression:

G.711 / G.726 / AAC /LPCM

Power Input:

Ultra PoE injector(POI-5001) 60W/ AC 24V ± 20% / DC 12V

Power Consumption:

43W (with IR & Heater on)

Storage Capacity:

Micro SD/SDHC/SDXC card Support Max 64Gb

Features

General:

Color, Brightness, Sharpness, Contrast

White Balance, Exposure Control

2DNR, 3DNR, NR by Motion

Masking, Text Overlay

PoE:

Ultra PoE injector(POI-5001) 60W/ AC 24V ± 20% / DC 12V

Security:

User and Administrator

Video:

Auto Flip

Motion Detection on Window x 4 sets

Privacy Mask Max 20 Mask

Up to 4 individually configurable streams in H.265/H.264/MJPEG .

Configurable resolution/frame rate/bandwidth LBR/VBR/CBR in H.265/H.264.

Audio:

G.711 / G.726 / AAC / LPCM
2 way,Line in /Line out

Performance

Number of Clients:

16

Frame Rate (fps):

H.265 HDR 3M @30fps + 3M @30fps
H.264 HDR 3M @30fps + 3M @30fps
MJPEG 1080p @30fps

Minimum illumination:

Color: 0.04 lux
B/W: 0.002 lux

Environment

Operating Temperature (°C):

-40°C ~ 50°C (-40°F ~ 122°F)

Operating Humidity (Non-condensing):

10% ~ 90%

Physical Specifications

Dimensions (W x D x H mm):

ø207.43 x 300.39 mm w/ Sunshield

Weight (g):

3.8 kg

Color:

White

Approval and Compliance

EMI/EMS:

CF/FCC

Safety:

IP66

Others:

ONVIF Profile S/G/Q support

Others

Supported Browsers:

Internet Explore (10.0+)

Order Information

FCS-4059

Package Contents

FCS-4059
Resource CD (User Manual, Utility)
Power Adapter
Mounting Kit



Optional Accessory



CAS-3261

Pole Thin Direct Mount Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.