



FCS-5096 Version: 1

Fixed IP Network Camera, 2-Megapixel, H.265/264, 802.3at PoE, 4.3X Optical Zoom, IR LEDs, Indoor/Outdoor, Vandalproof

Key Features

- Video compression: H.264/H.265
- Supports 4.3X optical zoom
- Features WDR (Wide Dynamic Range) to enhance visibility under extremely bright or dark environments
- Vandal-proof IK10-rated housing
- Weatherproof IP67-rated housing
- Built-in infrared LEDs for night viewing up to 50m
- Built-in Micro SDHC/SDXC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

2.8 to 12 mm

Port:

1 x RJ-45 10/100 Mbps PoE port
Power Connector
1 x MicroSDHC/ MicroSDXC card slot
1 X 1Vp 1Vp-p composite output (75 Ω/BNC)
1 X Terminal Block DI/DO (max 12 VDC, 30 mA)
1 x Audio in/Out
1 X Terminal Block 12 VDC

Button/Knob:

Reset Button

**Indicator:**

Power

IR Cut Filter:

Removable infrared-cut filter for day & night function

IR LED:

IR LEDs for illumination up to 50m

Shutter Time:

1/3 s to 1/100,000 s

Angle of View:

Horizontal field of view: 105°to 35°

Vertical field of view: 56°to 20°

Diagonal field of view: 126°to 40.5°

Pan/Tilt/Zoom:

4.3X Optical Zoom

Video Compression:

H.265, H.264, MJPEG(sub stream)

Resolution:

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Video Format:

AVI

Audio Compression:

G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM

Power Input:

12 V DC ± DC ± 25%, PoE (802.at)

Power Consumption:

12 VDC, 1.3A, max. 15.5W

PoE (802.3at, 42.5V to 57V), 0.5A to 0.1A, max. 17.5W

Data Transfer Rate:

32 Kbps to 16 Mbps

Features

General:

Motion Detection, Rotated Mode, Mirror, Color Adjustment (Brightness, Contrast, Saturation), Sharpness Adjustment, Anti-Flicker, Watermark, Privacy Mask

PoE:

PoE(802.3at)

Security:

One-key Reset, Heartbeat, Password Protection, IPv4, IPv6, File Management

Management:

Event Triggers (Network Disconnected, IP address Conflict, Illegal Login, HDD Full, HDD Error, Alarm Input, Alarm Output, Line Crossing Detection, Intrusion Detection, Face detection)

Video:

120dB Wide Dynamic Range, BLC, Auto White Balance (AWB), Privacy Mask (up to 5 region), 3D DNR

Audio:

8kHz/16kHz/32kHz/44.1kHz/48kHz

Performance

Number of Clients:

32

Storage Capacity:

Built-in microSD/SDHC/SDXC slot, up to 128 GB

Frame Rate (fps):**Main Stream**

50Hz: 50fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 60fps (1920 × 1080, 1280 × 960, 1280×720)

Sub Stream

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream

50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)

60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)

Minimum illumination:

Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR

Color: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR

Environment

Temperature (°C):

-30 °C to +60 °C (-22 °F to +140 °F)

Humidity (Non-condensing):

Humidity 95%

Physical Specifications

Dimensions (W x D x H mm):

144.13×332.73 mm (5.67"× 13.10")

Weight (g):

1893 g (4.17l b.)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Safety:

IK10

Environmental Test:

IP67

Others:

Manufactured in ISO-9001 and ISO-14001 certified factory

Others

Viewing Systems:

IE8+, Chrome 31.0-44, Firefox 30.0-51, Safari 8.0+

Compatibility:

ONVIF



Order Information

FCS-5096

Package Contents

FCS-5096

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.