



FEU-0512 Version: 1

# 5-Port Fast Ethernet Switch

The LevelOne FEU-0512 is a wire-speed, non-blocking networking device that provides 5 ports 10/100 Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

# **Key Features**

- Provides flexibility of 5x 10/100BASE-TX ports
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Quick and easy installation
- Supports 1K MAC address auto-learning and auto-aging
- Simple Plug and Play installation

# **Specifications**

# **System Specifications**

### Standards & Protocols:

IEEE802.3(10BASE-T),IEEE802.3u(100BASE-T),IEEE802.3az Energy Efficient Ethernet

#### Indicator:

Power, LINK/ACT

### Transmission Method:

Store- froward

### Power Input:

5V/0.6A

### Backplane (Gbps):

1Gbps

#### MAC Address Table:

1K

### **Features**

### General:

5 x 10/100Mbps

# **Performance**

www.level1.com Page 1 of 2

# Packet Forwarding Rate:

148800pps

# Environment

Operating Temperature (°C):

0-40°C

Operating Humidity (Non-condensing):

10%~90%

# **Physical Specifications**

Dimensions (W x D x H mm):

89\*86\*23mm

Weight (g):

?1KG

# **Order Information**

FEU-0512

# **Package Contents**

FEU-0512 Power Adapter Quick Installation Guide

No liability or responsibility for any errors or omissions in the content. Specifications are subject to change without notice.

All mentioned brand names are registered trademarks and property of their owners. Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.

www.level1.com Page 2 of 2