

FSW-0808TX Version: 6



8-Port Fast Ethernet Switch


The LevelOne FSW-0808 is a wire-speed, non-blocking networking device that provides 8 ports 10/100Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Easy Configuration and Maintenance

The LevelOne FSW-0808TX does not require software configuration. Users can immediately use any features of this product simply by attaching the cables and turning on the power. For instant error detection, the switch is equipped with a full range of LEDs to help you monitor and troubleshoot problems on your network.

Compact Size Design

This switch is compact specially designed to fit on the desktop or in other space-limited locations. The FSW-0808TX provides an ideal solution for businesses that crave a reliable network to exchange large data files and multimedia information with bandwidth-starving workgroup, departments, and offices.



1. Power Indicator
2. Link/Active Indicators

3. RJ-45 LAN Interface
4. External Power Socket

5. Magnetic Base

Key Features

- Provides flexibility of 8 x 10/100BASE-TX ports
- 10/100Mbps, full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Supports 1K MAC address auto-learning and auto-aging
- IEEE 802.3x Flow Control protects against lost packets for reliable data transmission
-
- Magnetic base for easy placement
- Quick and easy installation

Specifications

System Specifications

Standards & Protocols:

IEEE 802.3 10-BASE-T (Ethernet)

IEEE 802.3u 100-BASE-TX (Fast Ethernet)

IEEE 802.3x Flow Control (full-duplex flow control)

Buffer Memory:

96KB

Port:

8 x 10/100Base-TX RJ-45 Port

Indicator:

Power; Link/Active

Transmission Method:

Store-and-Forward

Power Input:

100-240V AC, 50-60 Hz, DC 5V, 1A, External Power Adapter

Power Consumption:

< 2.8W

Backplane (Gbps):

1.6Gbps

MAC Address Table:

1K

Data Rate:

10/100Mbps

Features

General:

Uplink: CSMA/CD

Flow Control: Half Duplex - Backpressure; Full Duplex - Pause frame

Performance

Packet Forwarding Rate:

100Mbps port - 148,000pps

10Mbps port - 14,880pps

Environment

Operating Temperature (°C):

Operating: 0°C ~ 40°C

Storage: - 40°C ~ 70°C

Operating Humidity (Non-condensing):

Storage: 5% ~ 90%

Operating: 10% ~ 90%

Installation:

Desktop and Magnetic Base

Physical Specifications

Dimensions (W x D x H mm):


125 x 69 x 30 mm

Approval and Compliance

EMI/EMS:

FCC, CE, RoHS

Diagram



Order Information

FSW-0808TX

Package Contents

FSW-0808TX

Power Adapter

Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.