

GEP-2021 20-Port Gigabit PoE Switch, 16 PoE Outputs, 2 x Gigabit RJ45, 2 x Gigabit SFP, 802.3at/af PoE, 270W

Product Images











Short Description

- 16 Gigabit PoE ports, 2 Gigabit ports and 2 Gigabit SFP slots.
- Total PoE power budget: 270W, up to 30W per port.
- IEEE 802.3af/at PoE compliant to simplify deployment and installation.
- Supports DIP switch configuration for VLAN mode and Default mode features.
- Supports port-based VLAN.
- 6KV surge protection, 6KV/8KV ESD protection.

Description

The GEP-2021 is LevelOne latest generation of 20-Port Gigabit Unmanaged PoE Switch, with 2 Gigabit RJ45 and 2 Gigabit SFP Uplink ports. also offers powerful DIP switch button configuration for VLAN mode and Default mode features. Switch that gives you a high-performance, low-cost, easy-to-use, seamless upgrade to boost your network to 1000Mbps. Increase the speed of your network backbone to a massive 40Gbps and bring Gigabit speeds all the way to your computers.

The GEP-2021 PoE-enabled switches features an IEEE 802.3af/at certified, better PoE functionality with 270W PoE power budget and usability. supports up to 16 ports at 15.4W, or 9 ports at 30 W to meet the increasing

power demands of users, giving you flexibility in power allocation for a variety of powered devices enabling you to scale your operations to meet business growth, operational cost savings, and ease of management.

Additional Information

Approval and compliance CE, RoHS Max. operating humidity (%) 90 Max. operating temperature (°C) 50

Max. storage temperature (°C) 85 Min. operating temperature (°C) -10 Min. storage temperature (°C) -40

Backplane (Gbps) 40Gbps Packet buffer 29.8Mpps

VLAN mode, Default mode Dip switch

Power, Link/Act, PoE usage rate(20%, 40%, 60%, 80%, Indicators

90%)

MAC address table 8K Flash memory size 4M

Mount 19" rack mount, Desk mount

Pin assignment and polarity 1/2 (+), 3/6 (-)

Power supply AC100-240V, 50/60Hz

Chipset RTL8332L

• IEEE 802.3 10-BASE-T (Ethernet) • IEEE 802.3u 100-BASE-Standards

TX (Fast Ethernet) • IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) • IEEE 802.3z 1000BASE-X (Gigabit Ethernet) •

IEEE 802.3 af/at

• Heat dissipation: 86,435 BTU/hr • MTBF: 250,000 hr **Features**

 $(25^{\circ}C)$

Product weight (kg) 4 Product breadth (mm) 442 285 Product depth (mm) 44 Product height (mm) Color Black

FAN 4015867223895

Model number GEP-2021

• GEP-2021 • Power Cord • 19" Rack Mount Kit • Quick Package contents

Installation Guide

Gigabit RJ45 2 Uplink ports (10/100/1000Base-T) Gigabit SFP 2 Uplink ports (1000Base-X SFP slots) 802.3af/at PoE 16 Downlink ports (10/100/1000Base-T)

Grade Commercial Data Rate **Gigabit Ethernet**

PoE Supported Yes Manageable No **Fanless** Nο

Total20.00 Concurrent ports Total270.00 PoE Power Budget

