

IGS-2108P Hilbert 8-Port Industrial Gigabit PoE Smart Lite Switch, 8 PoE Outputs, 802.3at/af PoE

Product Images



The LevelOne IGS-2108P provides high HW performance and environment flexibility for Enterprises. IGS-2108P is ideal to deliver management simplicity, optimum user experience, and lower total cost of ownership.

Additional Information

Harmonized System (HS) code	851762
Customs product code (TARIC)	8517620000
Features	L2 Switching Features 1. IGMP Snooping ● Supports IGMP Snooping ● Supports 128 groups 2. Link Aggregation ● Supports static link aggregation ● Supports 8 groups of aggregation, up to 4 ports per group 3. Port Mirroring ● One-to-one ● Many-to-Many 4. Support port isolation, port grouping VLAN ● Supports up to 32 VLANs (out of 4K VLAN IDs) ● Supports Port VLAN and 802.1Q VLAN ● Supports Port-based/802.1p/DSCP priority QoS ● Support 4 priority queues ● Port Speed Limit ● Storm Control
Management	● Web-based Graphic User Interface (GUI) ● Supports LevelOne IP Locator for easier IP management.
Data rate	Gigabit Ethernet
PoE Power Budget	Total 112.00
PoE Supported	Yes
Fanless	Yes
Manageable	Yes
Series	HILBERT series
Grade	Industrial
Approval and Compliance	● CE ● UKCA ● FCC Part 15, Subpart B Class B ● RoHS
Operating humidity	10% RH ~ 90% RH
Operating temperature	-40°C ~ 75°C
Storage humidity	5% RH ~ 95% RH
Storage temperature	-40°C ~ 85°C
Package Contents	● IGS-2108P ● Power Terminal Block ● Din-rail Mount Kit ● Quick Installation Guide ● Declaration of Conformity
Switching capacity	16 Gbps

Dimensions (W x D x H)	153 x 114 x 38 mm
Product weight (kg)	0.49 kg
Color	Black
EAN	4015867236192
Model Number	IGS-2108P
Power Redundancy	Dual Power Input
IP grade	IP30
Acoustic noise (dB)	0 dB (A)
Backplane (Gbps)	16
Dip switch	LOOP, VLAN ON/OFF
Flash memory size	2 MB
Packet forwarding rate	11.904 Mpps
Heat dissipation	40.94 (Btu/H)
Indicators	Power, Link/Act
Jumbo frame (KB)	9 KB
MAC address table	4 K
Mount	DIN rail mount
MTBF	43,800 hrs
Packet buffer	1.5 Mbits
Pin assignment and polarity	1/2 (+), 3/6 (-)
Port Configuration	8x 10/100/1000 Mbps PoE+ copper ports
Power consumption	120 W
Power input	Redundant Dual DC 12V/24V/48V
Power supply	VDC 44~57V
Power supply included	No

Standard

● IEEE 802.3 10-BASE-T (Ethernet) ● IEEE 802.3u 100-BASE-TX (Fast Ethernet) ● IEEE 802.3ab 1000BASE-T (Gigabit Ethernet) ● IEEE 802.3x Flow Control (full-duplex flow control) ● IEEE 802.3af Power over Ethernet ● IEEE 802.3at Power over Ethernet Plus ● IEEE 802.3az: Energy Efficient Ethernet ● IEEE 802.1D Spanning Tree Protocol (STP) ● IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)

