

KVM-3216 16-Port PS/2-USB VGA KVM

Product Images



Short Description

- 16-port Rackmount USB-PS/2 KVM switch with OSD

- Cascadable up to 16 units using daisy-chain cable
- Daisy-chaining distance up to 30 M
- Port capacity scalable up to 256 PCs (16 x KVM-3216)
- USB and PS/2 interface support on both console and PC side
- Support Microsoft and Logitech standard 5-key mouse and compatibles
- Computer selection and operation using front-panel push buttons , keyboard hotkeys and OSD Menu
- Support for DOS, Windows 95/98/SE/ME/2000/XP/Vista/7, Linux, MacOS, etc.
- Numerical LED display and LED indicators for easy bank/port status monitoring
- Active Sync Replication for DDC emulation
- Keyboard/mouse emulation to ensure compatibility to all machines and operating systems
- Extensive support for USB keyboards and mice
- One controller per port to keep keyboard and mouse alive
- Enhanced PS/2 mouse reset hotkeys for non-PnP OS such as Win NT 4.0 and Linux
- Buzzer sound for hotkey and port switching confirmation
- Autoscan period programmable 10 ~ 95 through OSD Menu option
- Password protection
- Auto-logout timeout support
- High VGA resolution 2048 x 1536
- PC side emulation module upgradable
- Firmware upgrad

Description

The LevelOne KVM-3216 16-port combo KVM switch enables users to control and manage a server farm or computers connected to the KVM switch with either the local console or remote console port. Local Console The KVM-3216 Combo KVM Switch is easy to connect to a keyboard and mouse with a VGA monitor through the local console port. This enables a user to control systems connected to the KVM switch directly. Remote Console In order to make use of the remote control feature.

Additional Information

Color	Black
EAN	4015867229392
Model Number	KVM-3216
Display Type	VGA
Installation	Rack Mount
Approval and Compliance	CE/FCC
Operating humidity	0% RH ~ 85% RH
Operating temperature	0°C ~ 40°C
Storage humidity	0% RH ~ 90% RH
Storage temperature	-10°C ~ 70°C
Package Contents	KVM-3216 Universal Power Adapter User Manual Upgrade Cable Daisy Chain Cable End Point Terminator
Dimensions (W x D x H)	410x165x44.5
Product weight (kg)	2.2
Indicators	Power Port LED x8
Resolution	2048 x 1536

