



- Compliant to Australia Electrical Equipment Safety System Compliance Level III
- Perfect for replacing traditional 18W 600mm T8 fluorescent tube
- No re-wiring needed for T8 fluorescent tube fixtures with starter and choke/coil ballast (CCG type T8 fluorescent)
- Single end power supply
- Shatter proof
- 50% power saving over T8 fluorescent tube
- Flickering-free
- LED starter included as a set
- UV- and IR-free light for less heat and protection for heat sensitive objects

Order Code	65778
General Data	00110
Lamp Socket	G13
Design	Double sheath shatter proof diffuser , Plastic over glass
Geometric Data	
Length (mm)	588mm
Diameter (mm)	27.5mm
Weight (g)	116g
Electric Data	
Wattage	9 W
Voltage	100-240 V AC
Power Factor	≥0.9
Operating Frequency	50/60 Hz
Photometric Data	
Luminous Flux (Im)	900
CRI	≥80
CCT	4000 K – Cool White
Luminous Intensity (cd)	160Cd
Beam Angle (°)	200°
Lifetime	30,000 hrs
Equivalent to (W)	18W





www.verbatim.com













Order Code	65778
Product Description	Verbatim LED CCG T8 9W 600mm 4000K Cool White 900Im with LED starter (AU version)

Technical Packaging Details		
Giftbox Barcode	6943760257786	
Inner Carton Barcode	16943760257783	
Outer Carton Barcode	26943760257780	
Pack Dimensions (LxWxH)	679mm x 33mm x 33mm	
Pack Weight	170g	
Carton Qty (Shipping Unit)	10	
Carton Dimensions (LxWxH)	725mm x 180mm x 90mm	
Cartons/Layer	10	
Layers/Pallet	10	
Units/Pallet	1000	