

Mode Number:DBC14-100

Technical Data Sheet

FileNumber:2022-10-27-02

- 1. Name of cable: Speaker Cable
- 2. P/O: DBC14-100 14AWG 2C
- 3. Designed of cable:
 - 3.1 Inner conductor: 105~~0~~.16±0.005mm Stranded Copper Ø1.89±0.05mm
 - 3.2 Insulation: PVC
 - 3.3 Size of Insulation: Ø2.7±0.1mm
 - 3.4 Color: Red/Black
 - 3.5 Two wires twisted to pairs
 - 3.6 PET Overlapped:
 - 3.7 Waterstop Overlapped:
 - 3.8 Tear line:
- 4. Jacket: PE (uvresistance,Not fire retardant)
 - 4.1 Colour: Black
 - 4.2 Size: Ø 7.0±0.3mm
 - 4.3 Wall thickness: ≈0.8mm
 - 4.4 Printing: Prolink 2 COND 14AWG 105 STRAND OXYGEN FREE COPPER DIRECT BURIAL WATER BLOCK TAPE CABLE Meter Marking
- 5. Electric data at 20°C:
 - 5.1 Conductor resistance: ≤8.6Ω/km
 - 5.2 Testing voltage: wire/wire 50Hz1min=1.5KV
 - 5.3 Operation voltage: 300V
- 6. Other requirement:
 - 6.1 Permissible temperature: -20°C---75°C
 - 6.2 Packing: 100M On non-returnable reel
 - 6.3 Test standard: This Technical Data Sheet

