




Excels in all applications.


Professional Series: Motorised lens HDCVI domes available in 2.0MP & 5.0MP

An excellent camera in all conditions with a wide range of compatible brackets, Professional Series domes from Securview offer up to 9x analogue resolution & easy adjustments via a motorised lens, all in a durable housing.

- Stream up to 5.0MP (2592 x 1944) at 20fps
- 2.7~13.5mm motorised varifocal lens with fixed iris
- Up to 700m video transmission over coaxial cable
- Smart infrared illumination, up to 30m range
- Superb low light colour images as low as 0.005lx
- True WDR (120dB) and 2D/3D noise reduction
- Dual voltage compatible: 12VDC and 24VAC
- IP67/IK10 for weather and vandal resistance



Up to 12x Image Resolution vs D1



Superb Low Light Performance



Dual Voltage Compatible

Model		CAM605		CAM659			
Camera	Image Sensor	1/2.8" 2.1 Megapixel CMOS		1/2.8" 5.0 Megapixel CMOS			
	Effective Pixels	1920(H) x 1080(V)		2592 (H) x 1944 (V)			
	Signal Noise Ratio	> 65dB					
	Lens	2.7 ~ 13.5mm F1.6 Motorised Lens; Fixed Iris					
	Angle of View	2.7 ~ 13.5mm F1.3 Motorised Lens; Fixed Iris					
	Focus	109° (wide) ~ 29° (tele)					
	Minimum Illumination	0.004Lux/F1.6, 30IRE, 0Lux IR Active		0.005 Lux at F1.3 (Colour) / 0 Lux IR Active			
	Electronic Shutter	1/4 ~ 1/100,000s					
	Day/Night	Auto (ICR) / Manual					
	Infrared Range	30m					
White Balance	Auto / Manual						
Noise Reduction	2D / 3D						
Gain Control	Auto						
Lighting Compensation	BLC / HLC / WDR (120dB)						
Video	Resolution	1080p (1920 x 1080) to CIF (352 x 288)		5.0MP (2592 x 1944) to CIF (352 x 288)			
	Frame Rate	25fps (1080p and lower)		20fps (5.0MP), 25fps (4.0MP and lower)			
	Transmission Distance	Rated for up to 700m via 75-3 coaxial cable (performed in ideal test conditions)					
DORI	Distance	Detect	44m (wide) / 153m (tele)		64m (wide) / 222m (tele)		
		Observe	18m (wide) / 61m (tele)		26m (wide) / 89m (tele)		
		Recognise	9m (wide) / 31m (tele)		13m (wide) / 44m (tele)		
		Identify	5m (wide) / 15m (tele)		6m (wide) / 22m (tele)		
Interface	Audio Input	N/A		1 channel in			
	Alarm Interface	N/A					
	Video Output	1 x HDCVI / AHD / TVI / Composite Video Output (DIP switch)					
	Synchronisation	Internal					
Environmental	OSD Menu	Support					
	Ingress Protection	IP67					
	Vandal Resistant	IK10					
	Housing	Metal, Polycarbonate					
	Power Input	12VDC / 24VAC					
	Power Consumption	< 5.9W		< 11.8W			
	Dimensions	Ø122 x 89mm					
Weight	0.43kg		0.48kg				
Operating Environment	-30° to 60°C / RH90% (max)						
Accessories	Diagram						
	Accessories						
Models	Junction Box (MB1048)	In-Ceiling Mount (MB1061)	Wall Mount (MB1043)	Wall Mount Rain Shield (MB1055)	Ceiling Extension (MB1060 + MB1057)	Right Angle Wall Mount (MB1060+ MB1054)	Pole Mount (MB1027 + MB1043)

Your local Securview™ HDCVI solutions professional: