



4K Coaxial CCTV solutions.

Professional Series: 8.0MP Motorised Pro HDCVI surveillance kits in 8 & 16 channels

Securview[™] Motorised lens Pro HDCVI surveillance kits are high performance CCTV systems, ideal for homes and businesses. Capture hidden details with video streaming up to, and retrofit existing cameras with Victory Synergy.

- Records up to UHD/4K 8.0MP (3840 x 2160) at 7fps
- 60m IR, True WDR (120dB) and 2D/3D noise reduction
- Pre-fitted 2TB / 4TB surveillance-grade HDDs
- IP67 rated aluminum housing cameras

- Native Ultra HD live view on 4K monitors via HDMI
- Up to 700m video transmission over coaxial cable
- HDCVI/AHD/TVI/Analogue switchable cameras
- Remote view for iOS, Android & Windows smart device



Ultra HD Recording Over Coax



Victory Synergy Compatibility



Pro 4K Motorised Turrets

Choose from three comprehensive, ready to install packages.

The Securview™ Professional Series offers complete 4 & 8 camera HD-over-coax surveillance packages, purpose-built for rapid installation and impressive results.



Kit Specifications

For full specifications and bracket compatibility, please see the individual web entry or datasheet.

DVR Model	DVR611	DVR612
Product Image	888-5 = 111 - 7	
Video Input	8 channel	16 channel
C	Coaxial: 8 channels up to 8.0MP/7fps (HDCVI, HDTVI, AHD), 960H/25fps (analogue)	Coaxial: 16 channels up to 8.0MP/7fps (HDCVI, HDTVI, AHD), 960H/25fps (analoque)
Camera Configurations	Network: Add 8 channels up to 8.0MP Max 128Mbps Incoming Bandwidth	Network: Add 16 channels up to 8.0MP Max 128Mbps Incoming Bandwidth
Video Output	1 x HDMI , 1 x VGA	
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)	
Video Compression	H.265+ / H.265 / H.264+ / H.264	
Remote View	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)	
Internal HDD	2 x SATA port up to 10TB max, 20TB HDD Capacity	

Camera Model	CAM656	
Product Image		
Image Sensor	Image Sensor 1/2″8.0 Megapixel CMOS	
Lens	3.7~11mm F1.6 Motorised Lens	
Angle of View	112° ~ 46°	
Lighting Compensation	BLC / HLC / WDR (120dB)	
Video Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)	
Infrared Range	60m range, Auto/manual on/off control	
Frame Rate	15fps (8.0MP) / 20fps (6.0MP) / 25fps (4.0MP and lower)	
Housing	Aluminum, IP67 weather-rated	
Power Supply	12VDC	
Suggested Products	Junction Box (VSBKTA130E), Corner Wall Mount (VSBKTA151), Triple Clamp Pole Mount (VSBKTA150), Dual Clamp Pole Mount (VSBKTA152E)	

Your local Securview™ HDCVI solutions professional: