

- Frosted Dome
- No UV emission
- Slim and elegant heatsink design
- Free of mercury and heavy metal to protect environment
- B22 lamp base
- High Lumen output, equivalent to 100W incandescent blub (1600lm)
- High efficacy (>100lm/W)
- Lifetime of 15,000 hrs
- Triac dimmable (with Leading/Universal/Trailing



Order Code 65262

General Data

Lamp Socket B22
Design Frosted Dome

Geometric Data

Length (mm) 134.00
Diameter (mm) 60.00
Weight (g) 160




Electric Data

Wattage 15 W
Voltage 220-240 V AC
Power Factor ≥ 0.50
Operating Frequency 50/60 Hz

Photometric Data

Luminous Flux (lm) 1600
CRI ≥ 80
CCT 4000 K – cool white
Luminous Intensity (cd) 210
Beam Angle (°) 220°
Lifetime 15,000 hrs

Equivalent to (W)





Order Code	65262
Product Description	Verbatim LED Classic-A B22 15W 4000K CW 1600LM 220-240V Dimmable

Technical Packaging Details

Giftbox Barcode	6943760252620
Inner Carton Barcode	N.A.
Outer Carton Barcode	26943760252624
Pack Dimensions (HxWxL)	150 mm x 72 mm x 72 mm
Pack Weight	195g
Carton Qty (Shipping Unit)	10
Carton Dimensions (HxWxL)	160 mm x 156 mm x 375 mm
Cartons/Layer	11
Layers/Pallet	5
Units/Pallet	550