



Affordable CCTV solutions.

Compact Series: 4.0MP motorised lens IP surveillance kits in 4, 8 & 16 channels

The Watchguard™ motorised lens surveillance kits offer cameras with up to 4x optical zoom and built in PoE for rapid installation. They boast high performing CCTV solutions that are ideal for any home or business, at an affordable price.

- Records up to 4.0MP (2560 x 1440 pixels) at 20fps
- Up to 60m infrared range; true day/night (auto ICR)
- Motion & face detection, region of interest and more
- Pre-fitted 1TB / 2TB / 4TB surveillance-grade HDDs
- IP67 rated, metal housing cameras; IK10 rated domes
- Native Ultra HD live view on 4K monitors via HDMI
- Built-in Power over Ethernet (PoE) for easy installation
- Power via 12VDC or Power over Ethernet (802.3af)
- Mix & match any equivalent price dome/bullet camera
- Remote view for iOS, Android & Windows Phone







Impressive double full HD resolution

Built-in PoE for plug & play install

Remote view on your device



Choose from three comprehensive, ready to install packages.

The Watchguard™ Compact Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.

Kit Model	NVR353	NVR354	NVR355
Kit Image	An An I I I I I I I I I I I I I I I I I	The state of the s	
Network Video Recorder	NVR316 with 4 Port PoE & 1 x SATA Bay	NVR317 with 8 Port PoE & 1 x SATA Bay	NVR318 with 16 Port PoE & 2 x SATA Bay
Internal Storage	1TB Surveillance HDD	2TB Surveillance HDD	4TB Surveillance HDD
Standard Cameras	2 x CAM457 4.0MP 30m IR Vandal Dome 2 x CAM463 4.0MP 60m IR Bullet	4 x CAM457 4.0MP 30m IR Vandal Dome 4 x CAM463 4.0MP 60m IR Bullet	8 x CAM457 4.0MP 30m IR Vandal Dome 8 x CAM463 4.0MP 60m IR Bullet
Included Accessories	1 x 1.5m CAT5 patch cable for networking / 1 x 1m HDMI output cable / 1 x NVR Remote and 1 x Mouse *Camera cablina sold separately*		

Kit Specifications

or full specification	1 7.1	<u> </u>		
Kit Model	NVR316	NVR317	NVR318	
Product Image				
Video Input	4 channel	8 channel	16 channel	
Video Output	1 x HDMI , 1 x VGA			
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)			
ncoming Bandwidth	80Mbps		200Mbps	
/ideo Compression	H.265 / H.264			
Bit Rate	16 ~ 20Mbps per channel			
Ethernet	1 x RJ-45 port (10/100Mbps)		1 x RJ-45 port (10/100/1000Mbps)	
PoE	4 ports (IEEE802.3at/af)	8 ports (IEEE802.3at/af)	16 ports (IEEE802.3at/af)	
Remote View	iOS (iPho	iOS (iPhone, iPad) / Android devices / Windows Phone* (limited functionality)		
nternal HDD	1 x SATA port up to 10TB max, 10TB HDD Capacity 2 x SATA port up to 10TB max, 20TB HDD Capacity			
Camera Model	CAM463	CAM457	CAM456 (Optional)	
Product Image		erkitaen.		
mage Sensor	1/3" 4.0MP Progressive Scan CMOS			
	2.8mm~12mm F1.8 Motorised Varifocal Lens, Horizontal: 94°~33°, Vertical: 51°~19° (4x Optical Zoom)			
.ens	2.8mm~12mm F1.8 M	otorised Varifocal Lens, Horizontal: 94°~33°, Vertical: 51°~	·19° (4x Optical Zoom)	
	2.8mm~12mm F1.8 M	otorised Varifocal Lens, Horizontal: 94°~33°, Vertical: 51°~ BLC / HLC / Digital WDR	-19° (4x Optical Zoom)	
ighting Compensation		BLC / HLC / Digital WDR 4.0MP (2560 x 1440) to CIF (352 x 288)		
ens ighting Compensation Resolution nfrared Range	2.8mm~12mm F1.8 M 4 x Infrared LED, 60m range Auto/manual on/off control	BLC / HLC / Digital WDR	-19° (4x Optical Zoom) 2 x Infrared LED, 50m range Auto/manual on/off control	
ighting Compensation	4 x Infrared LED, 60m range Auto/manual on/off control	BLC / HLC / Digital WDR 4.0MP (2560 x 1440) to CIF (352 x 288) 2 x Infrared LED, 30m range	2 x Infrared LED, 50m range Auto/manual on/off control	
Lighting Compensation Resolution Infrared Range	4 x Infrared LED, 60m range Auto/manual on/off control N	BLC / HLC / Digital WDR 4.0MP (2560 x 1440) to CIF (352 x 288) 2 x Infrared LED, 30m range Auto/manual on/off control	2 x Infrared LED, 50m range Auto/manual on/off control s)	
Lighting Compensation Resolution Infrared Range Frame Rate	4 x Infrared LED, 60m range Auto/manual on/off control N Motion Detection (4	BLC / HLC / Digital WDR 4.0MP (2560 x 1440) to CIF (352 x 288) 2 x Infrared LED, 30m range Auto/manual on/off control lain Stream: 4.0MP (1 ~ 20fps) / Sub Stream: D1 (1 ~ 20fp	2 x Infrared LED, 50m range Auto/manual on/off control s) ones), Smart Infrared	

JunctionBox(MB1048), Dual Clamp Pole Mount

(MB1027), Rain Cover (MB1055), Right Angle Wall

Mount (MB1043), Recessed Ceiling Mount

(VSBKTB200)

Junction Box (MB1048),

Dual Clamp Pole Mount (MB1027),

Right Angle Wall Mount (MB1043)

Your local Watchguard™ IP surveillance professional:

Suggested Products

Junction Box (MB1049),

Corner Wall Mount (MB1026), Dual

Clamp Pole Mount (MB1027)