

**6.0**  
MEGAPIXEL



# Protect home & small business.

## L-Series CCTV Kits: 6.0MP fixed lens surveillance kits in 4 & 8 Channels

The Watchguard™ L-Series surveillance kits are a high performing CCTV system, ideal for homes and small businesses. These CCTV kits includes a built-in PoE NVR and weather resistant cameras, capable of recording beyond HD resolution.

- Records up to 6.0MP (3072 x 2048) at 25fps
- Up to 30m infrared range; true day/night (auto ICR)
- Pre-fitted 1TB / 2TB SkyHawk surveillance HDDs
- IP67 weather rated metal housing
- Native Ultra HD live view on monitors via HDMI
- Remote view for iOS, Android & Windows smart device
- Motion detection, region of interest and more
- Built-in Power over Ethernet (PoE) for easy installation



Beyond HD Recording



Built In Power Over Ethernet



Remote View From Your Device



## Choose from two comprehensive, ready to install packages.

The Watchguard™ L Series offers complete 4 & 8 channel network surveillance packages, purpose-built for rapid installation and impressive results.

Kit Model	NVRKIT-L461-4C	NVRKIT-L862-4C
Kit Image		
Digital Video Recorder	4 Channel Compact NVR with pre-installed 1TB SkyHawk Surveillance HDD	8 Channel Compact NVR with pre-installed 2TB SkyHawk Surveillance HDD
Standard Cameras	4 x 6.0MP IR Fixed-Focal Eyeball Network Cameras	4 x 6.0MP IR Fixed-Focal Eyeball Network Cameras

## Kit Specifications

For full specifications and bracket compatibility, please see the individual web entry or datasheet.

NVR Model	NVR4COM3	NVR8COM3
Product Image		
Video Input	4 Channel	8 Channel
Video Output	1 x HDMI, 1 x VGA	
Recording Resolution	Configurable from 8.0MP (3840 x 2160) to CIF (352 x 288)	
Video Compression	H.265+ / H.265 / H.264+ / H.264	
Remote View	iOS (iPhone, iPad) / Android devices	
Internal HDD	1 x SATA III port, up to 10TB	

Camera Model	VS1PL-6DIRG
Product Image	
Image Sensor	1/2.7" CMOS
Lens	Lens 2.8mm F1.6 Fixed-Lens
Angle of View	103.0°
Lighting Compensation	BLC / HLC / WDR 120dB
Video Resolution	3072 (H) x 2048 (V)
Infrared Range	30m Range, Auto/Manual On Off Control
Frame Rate	Main Stream: 6.0MP (1 ~ 25fps) Sub Stream: D1 (1 ~ 25fps)
Housing	Metal, IP67 weather-rated
Power Supply	12 VDC/PoE
Suggested Products	Junction Box ( VSBKTA136 ) Right Angle Wall Mount ( VSBKTB204W ) Pole Mount ( VSBKTA152E )

Your local Watchguard™ IP surveillance professional: