



Wiretek

WEB214

## WEBCAM USB FULL-HD 1080p - PREMIUM AUTO FOCUS - PREMIUM TAWANESE CHIPSET

Upgrade your web casting quality with this premium Taiwan chipset camera from Wiretek designed for excellent picture quality up to 1080 resolutions at 30 Hz. Suitable for webcasting, Skype, Zoom, etc. Kit includes a three legged metal goose-neck type Desk-top stand using the standard camera mount thread is removable for compatibility with other stands. Weighted base with 360 rotateable and tiltable joint for adjusting the viewing angle. Folds out to be a monitor/laptop clamp to sit on the screen edge. Optional flip type lens cap for mechanical assured privacy. Attached 1.2m USB-A lead that's directly Plug-N-Play to Windows™, Linux-2.6.26 or Later, MAC-OS X 10.4.8 or above and Android 4.0 or above with UVC. No drivers required. Attractively packaged for resale.



## WEB214



Wiretek Premium Grade Webcam using the latest Taiwanese grade chipset  
Quickly Auto Focus. Distance from 50mm to infinity for a sharp and clear image.  
Noise reducing digital microphone with echo cancelling for clear and natural sound.  
Automatic low-level light correction with HDR technology works well in even dim lighting  
Suitable for most software: Skype, Youtube, Facebook, Xsplit, Zoom, Hangouts, etc.  
Quick & easy setup instantly gets you up and running immediately with your application  
Privacy protector (Detachable) webcam cover prevents web hackers spying on you  
Kit includes desk-stand, monitor clamp, connection cable, all attractively boxed  
Upgrade your web camera today to full HD for a more comfortable realistic image



Phone: 02 9797 9866  
Web: [www.wes.net.au](http://www.wes.net.au)  
Email: [sales@wes.net.au](mailto:sales@wes.net.au)



Wiretek

WEB214



Specification	
Wiretek	WEB214
Sensor	REALTEK 567, 2132-H01
Pixels	1/4 2MEGA
Resolution	1920*1080P/ 30fps
Focusing mode	Auto Focus
Focus range	0.5-50meters
Field of view	90°
Camera Rotation	360°
Encoding format	MJPEG / YUY2 etc
Microphone	Digital mic
Noise Cancelling	Auto
Voice pickup range	Support 3-5m far field pickup
Audio encoding format	PCM
Audio bit rate	8KHZ-48KHZ
Protocol compatible	USB VIDEO Class (UVC)
Power supply	USB DC5V
Interface	USB 2.0
Driver	No need, Plug and play
Image Control Function	Auto Exposure Control (AEC)
	Auto White Balance (AWB)
	Auto Gain Control (AGC)
Compatible System	WinXP/Vista/Win7/Win8/Win10
	Linux with UVC (2.6.26 or above)
	MAC-OS X v10.6 or above
	Android v5.0 or above
Operating temperature	0~60 °C
Storage temperature	-20 - 75 °C
Accessories	USB cable :TPE CABLE Length 1.5 m
	Port: USB2.0, TYPE A
	Lens cap
	tripod



Phone: 02 9797 9866

Web: [www.wes.net.au](http://www.wes.net.au)

Email: [sales@wes.net.au](mailto:sales@wes.net.au)