

Eaton 5E650IUSB

Catalog Number: 5E650IUSB

Eaton 5E UPS USB, 650 VA, 360 W, Input: C14, Outputs: (4) C13, Tower

General specifications

Product Name	Catalog Number
Eaton 5E UPS	5E650IUSB
UPC	Product Length/Depth
743172047571	288 mm
Product Height	Product Width
148 mm	100 mm
Product Weight	Warranty
4.64 kg	2 year
Compliances	Certifications
CE Marked	EAC
	IEC/EN 62040-2
	CE
	IEC/EN 62040-1
Catalog Notes	
EMEA & GLOBAL	



Product specifications

Secondary frequency - max

60 Hz

Wattage

360 W

Form factor

Tower

Includes network card

No

Input connection

C14

Input voltage - min

162 V

Output voltage - max

280 V

Secondary frequency - min

50 Hz

Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

Battery type

Sealed, lead-acid

Efficiency

95

Special features

Automatic Voltage Regulation (AVR)
Saves space with a compact tower design
HID-compliant USB port, for automatic integration with major operating systems (Windows/Mac OS/Linux)
Data line protection to ensure that the internet line (including xDSL) is protected against surges

Construction type

Resources

Brochures

[Eaton UPS Services Quick Guide 2021](#)

[Eaton UPS and battery services](#)

Free standing model

Output voltage - min

170 V

Color

Black

Extended battery capability

No

Output voltage range

170-280 V

Topology

Line-interactive

Surge protection

Yes

Runtime at half load

8 min

Input nominal voltage

230V default (220/230/240V)

Input frequency range

45-63 Hz

Input voltage - max

290 V

Voltage type

AC

Phase (output)

1

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Auto shutdown function

Yes

Number of Outputs C13

4

Operating temperature - min

0 °C

VA rating

650 VA

Potential free switch contact

No

Receptacle

(4) C13

Phase (input)

1

Package contents

(2) IEC-IEC output cables

User manual

Noise level

<40 dB at 1 meter

Feed type

1

Runtime graph

View runtime graph

User interface

LEDs

Battery quantity

1

Operating temperature - max

40 °C

Voltage

230V

Temperature range

0° to 40°C (32° to 104°F)

Ethernet interface

No

Communication

USB port (HID compliant)

Relative humidity

0-90% non-condensing

Output apparent power

650 VA

Rack mounting kit

No

Output frequency

50/60 Hz

Runtime at full load

30 sec

Type of interface

USB

Primary frequency - min

45 Hz

Battery rating

12 V / 7 Ah

Type

UPS

Output nominal voltage

230V

Expansion slots

No

Input voltage range

162-290 V

Nominal frequency

50/60 Hz

Primary frequency - max

63 Hz

Altitude

2000 m



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia