Richard Foot Pty Ltd

MATERIAL SAFETY DATA SHEET

PRODUCT: RF CONTACT CLEANER LUBRICANT

PRODUCTION IDENTIFICATION

Trade Name: UN No: 1950

Other Name: Dangerous Goods Class: 2

Flammable Gas Subsidiary Risk: Hazchem Code: 2Y Poisons Schedule:

Classified as Hazardous according to criteria of Worksafe Australia

Use

A mixture of synthetic lubricant and solvents for cleaning electrical and electronic connectors Packaged in 175gm (250ml) aerosol cans – Apply from aerosol.

Physical Description/Properties

Manufacturers Code: Aerosol - 60.0064

Low viscosity solvent/lubricant mix, medium flammable

Flash Point: 49 Deg C (solvent) Auto Ignition Temp: Not Available

Flammable Limits in Air: vol%: Lower 1 Upper 7

Ingredients

Hydrocarbon Propellant

Chemical Entity	CAS NO.	Proportions %
Petroleum distillates	[64742-47-8]	High > 60%
Alcohol	[70914-20-4]	Low < 10%
Polyglycol	[9003-13-8]	Low < 10%

Page 1

Richard Foot Pty Ltd

RF CONTACT CLEANER LUBRICANT

HEALTH HAZARD INFORMATION

Health Effects

Swallowed: Low order of toxicity. May cause irritation to mouth, throat and digestive system.

Eye: Irritant

Skin: Low order or toxicity. Irritant also causes defaulting of skin.

Inhaled: May irritate nose and respiratory tract, may cause drowsiness and headache.

First Aid

Swallowed: Do not induce vomiting because of risk of aspiration. Give 250mls of milk to drink. "Liquid

paraffin" may slow gastric absorption.

Eye: Irrigate eye with copious quantities of water for at least 15 minutes. Skin: Wash off with soap and water. Remove contaminated clothing.

Inhaled: Move to fresh air, keep patient warm and at rest. If loss of consciousness, give oxygen and if

breathing stops give artificial respiration.

Advice to Doctor: Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Limits

TLV 100 ppm

Engineering Controls

Ensure adequate ventilation to keep airborne concentrations below exposure standard.

Personal Protection

Not normally necessary

Flammability

Avoid sources of ignition.

Page 2

Richard Foot Pty Ltd

RF CONTACT CLEANER LUBRICANT

SAFETY HANDLING INFORMATION

Storage/Transport

Store in a cool dry area

Packaging/Labeling

UN NO.1950 Class 2 flammable gas Sub Risk None Allocated Hazchem Code 2Y Pack Group N/A Shipping Name Aerosols

Spills and Disposal

Dispose of in accordance with local rules and regulations.

FIRE AND EXPLOSION HAZARD

Fire/Explosion

Flammable material Hydrocarbon propellant

Extinguishing Media

Use foam or dry chemical

CONTACT: TECHNICAL MANAGER (02) 9979 8311

EMERGENCIES: (Mobile 0411 834 321)

DATE OF ISSUE: 1/03/2010

Page 3