





# Completely wireless CCTV.

## Watchguard<sup>™</sup> Reolink Argus 3 Pro 1440p wireless bullet camera

The Watchquard™ wireless bullet camera is a portable CCTV solution that can be installed anywhere, indoors and outdoors. Enjoy hassle free installations at any location with no wiring, WiFi or power adapter required.

- Stream up to Full HD / 2K (2560 x 1440) at 15fps
- Fixed lens with wide 122° diagonal viewing angle
- 10m IR, capture details in low light conditions
- Two way talk with built-in microphone & speaker
- Smart PIR motion sensor, with up to 10m range
- IP65 rated weather resistant housing for outdoors
- Power via power supply (included) or solar panel
- View footage & receive alerts via the free Reolink app



4.0 MP Image Resolution











### **Install Anywhere**

100% wireless and portable, install in homes, offices and more



#### WiFi Connection

Easy setup & connection over the WiFi network



#### **Solar Powered**

Connect the camera to the Reolink™ solar panel for non-stop sustainable power (Included)



#### **Remote View**

Live view footage, 2 way talk, receive alerts & more via a smartphone

Specification	ns	Watchguard™ Reolink Argus 3 Pro 1440p Wireless Bullet
Product Image		Watchguald Reollik Algus 3 F10 1440p Wireless Bullet
Ordering Information		REO-AG3PRO: Reolink Camera
Image Sensor		1/3 " Starlight CMOS Image Sensor
Effective Pixels Infrared		2560 (H) x 1440 (V)
Infrared		6 x IR LEDs, 10m range
PIR Detection		Up to 10m (adjustable), 100° (H) PIR detecting angle
Lens / Iris		Fixed Lens (16x Digital Zoom)
Field of View		Diagonal: 122°
Focus		Fixed
Resolution		1440p / 4.0MP (2560 x 1440)
g.	Main	1440p (1 ~ 15fps)
Frame Rate	Sub	N/A
	Third	N/A
Video Com	ression	H.265
Operating Frequency		2.4GHz/5GHz
Audio Interface		High quality speaker & microphone
Audio Alerts Other Alerts		Siren / Customised voice recordable alerts
		Instant email alerts and push notifications
Local Storage		Supports up to 128GB micro SD card
Cloud Storage		Supports Reolink Cloud
Battery		6000mAh rechargeable battery (Battery life varies based on settings, usage and temperature)
<u>g</u> Solar		Can be powered by Reolink solar panels
DC Power		Can be powered by 5V/2A USB power adapter
Weather Resistance		IP65
Solar DC Power Weather Resistance Operating Conditions		-10°C ~ 55°C
Dimensions		121mm x 90mm x 56mm
Net Weight		0.33kg (with battery)