



Peak quality & versatility.

Professional Series: Motorised lens HDCVI bullet available in 8.0MP

With superior 80m infrared illumination, 4K resolution and ultra low light colour, the G-Body series from Securview captures clear footage at all hours, featuring a motorised varifocal lens for easy remote image adjustment.

- Stream up to UHD/4K/8.0MP (3840 x 2160) at 15fps
- Motorised varifocal 3.7~11mm lens with fixed iris
- Large 1/2" sensor for excellent low light performance
- Smart infrared illumination, up to 80m range
- HDCVI / AHD / TVI / CVBS switchable via DIP switch
- Up to 700m video transmission over coaxial cable
- True WDR (120dB) and 2D/3D noise reduction
- IP67 rated weather resistant metal housing



Ultra HD Recording Over Coax



Compatible With Any Coax DVR



Superb Low Light Performance

Model		VSCVI-8BIRMG			
Camera	Product Image				
	Camera Style	G Body			
	Image Sensor	1/2" 8.0 Megapixel CMOS			
	Effective Pixels	3840 (H) x 2160 (V)			
	Signal Noise Ratio	> 65dB			
	Lens	3.7mm ~ 11mm F1.5 Motorised Lens			
	Angle of View	112°			
	Focus	Fixed / 1.8m Min. Focus Distance			
	Minimum Illumination	0.005 Lux at F1.5 (Colour) / 0 Lux IR Active			
	Electronic Shutter	1/4 ~ 1/100,000s			
	Day/Night	Auto (ICR) / Colour / B&W			
	Infrared Range	80m			
	White Balance	Auto / Manual			
	Video	Noise Reduction	2D / 3D		
Gain Control		Auto			
Lighting Compensation		BLC / HLC / WDR (120dB)			
DORI	Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)			
	Frame Rate	15fps (8.0MP) / 20fps (6.0MP) / 25fps (4.0MP and lower)			
	Transmission Distance	Rated for up to 700m via 75-3 coaxial cable (performed in ideal test conditions)			
Interface	DORI Distance	Detect (25px/m) 83m (wide) / 190m (tele)	Observe (63px/m) 33m (wide) / 76m (tele)	Recognise (125px/m) 17m (wide) / 38m (tele)	Identify (250px/m) 8m (wide) / 19m (tele)
	Audio Input	Built-in Microphone / 1 Input			
	Alarm Interface	N/A			
	Video Output	1 x HDCVI / AHD / TVI / Composite video output (switchable via DIP switch)			
	Synchronisation	Internal			
Environmental	OSD Menu	Support			
	Ingress Protection	IP67			
	Vandal Resistant	N/A			
	Housing	Aluminium			
	Power Input	12VDC			
	Power Consumption	< 12.5W			
	Dimensions	244 x 90 x 90mm			
Accessories	Weight	0.76kg			
	Operating Environment	-30° to 60°C / RH90% (max)			
Accessories	Diagram				
	Accessories				
	Models	Junction Box (VSBKTA130E)		Pole Mount (VSBKTA130E + VSBKTA152E)	
		Corner Mount (VSBKTA130E + VSBKTA151)			

Your local Securview™ HDCVI solutions professional: