



Accurate motion detection.

Professional Series: Fixed lens 8.0MP HDVCI bullet with dual motion detection

Deliver accurate motion detection in any outdoors setting. This 4K fixed lens bullet series combines pixel & PIR motion detection, eliminating false alarms and only activating when both motion & heat are detected at the same time.

- Stream up to UHD/4K/8.0MP (3840 x 2160) at 15fps
- 2.8mm fixed lens with 110° viewing angle
- Dual pixel motion & infrared detection technology
- Infrared illumination at up to 20m range
- HDCVI / AHD / TVI / CVBS switchable via DIP switch
- Up to 700m video transmission over coaxial cable
- True WDR (120dB) and 2D/3D noise reduction
- IP67 rated weather resistance metal housing



Ultra HD Recording Over Coax



Compatible With Any Coax DVR



Dual Motion Detection Technology

Model		VSCVI-8BIRP			
Camera	Product Image				
	Camera Style	P Body			
	Image Sensor	1/2" 8.0 Megapixel CMOS			
	Effective Pixels	3840 (H) x 2160 (V)			
	Signal Noise Ratio	>65dB			
	Lens	2.8mm F1.6 Fixed Lens			
	Angle of View	111°			
	Focus	Fixed / 1.8m Min Focus Distance			
	Minimum Illumination	0.005 Lux at F1.6 (Colour) / 0 Lux IR Active			
	Electronic Shutter	1/4s ~ 1/100,000s			
	Day/Night	Auto (ICR) / Colour / B&W			
	Infrared Range	20m			
	White Balance	Auto / Manual			
	Video	Noise Reduction	2D / 3D		
Gain Control		Auto			
Lighting Compensation		BLC / HLC / WDR (120dB)			
DORI	Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)			
	Frame Rate	15fps (8.0MP) / 20fps (6.0MP) / 25fps (4.0MP and lower)			
	Transmission Distance	Rated for up to 700m via coaxial cable (performed in ideal test conditions)			
	DORI Distance	Detect (25px/m) 84m	Observe (63px/m) 34m	Recognise (125px/m) 17m	Identify (250px/m) 8m
Interface	Audio Input	Built-in Microphone / 1 Input			
	Alarm Interface	N/A			
	Video Output	1 x HDCVI / AHD / TVI / Composite video output (switchable via DIP switch)			
	Synchronisation	Internal			
	OSD Menu	Support			
Environmental	Ingress Protection	IP67			
	Vandal Resistant	N/A			
	Housing	Aluminium (front cover) + Plastic (rear barrel)			
	Power Input	12VDC			
	Power Consumption	< 5.3W			
	Dimensions	147 x 72 x 83mm			
	Weight	0.25kg			
Operating Environment	-10°C ~ +50°C/RH 95% (max)				
Accessories	Diagram				
	Accessories				
Models	Junction Box (VSBKTA134)		Pole Mount (VSBKTA134 + VSBKTA152E)		

Your local Securview™ HDCVI solutions professional: