



All-in-one CCTV solutions.

Professional Series: 8.0MP Surveillance Kits available with 4, 8 & 16 cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in Power over Ethernet for fast installations. Mix & match any equivalent priced dome or bullet camera to suit your installation needs.

- Records Ultra HD/8.0MP (3840 x 2160) up to 15fps
- 8.0MP True WDR 50m IR dome cameras in 2.8mm
- 8.0MP True WDR 40m IR bullet cameras in 2.8mm
- Remote view in seconds with setup via QR code
- IVS with tripwire, intrusion, motion detection & more
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet (ePoE for 8/16 channel)
- Pre-installed 2TB/4TB/2 x 4TB surveillance grade HDD(s)
- Remote view for iOS, Android & Windows Phone
 *Camera cabling sold separately



Ultra HD Recording & Live View



Extended PoE (ePoE) up to 800m



Comprehensive Remote View



Choose from three comprehensive, ready to install packages.

The VIP Vision Professional Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.







4 Chann

4 Channel Professional NVR

- · 4 port Power over Ethernet NVR
- Records 8.0MP at 15fps
- Pre-installed 2TB hard disk drive (additional backup via USB device or network)

4 x 8.0MP Infrared Cameras

- 2 x bullet and 2 x dome cameras
- 2.8mm (112°) fixed lens
- Stream up to 8.0MP (3840 x 2160)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- Camera cabling sold separately

8 Channel

8 Channel Professional NVR

- 8 port Extended Power over Ethernet NVR
- · Records 8.0MP at 15fps
- Pre-installed 4TB hard disk drive (additional backup via USB device or network)

8 x 8.0MP Infrared Cameras

- 4 x bullet and 4 x dome cameras
- · 2.8mm (112°) fixed lens
- Stream up to 8.0MP (3840 x 2160)
- · IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

NVR367

6 Channel

16 Channel Professional NVR

- 16 port Extended Power over Ethernet NVR
- Records 8.0MP at 15fps
- 2 x Pre-installed 4TB hard disk drive (additional backup via USB device or network)

16 x 8.0MP Infrared Cameras

- 8 x bullet and 8 x dome cameras
- · 2.8mm (112°) fixed lens
- Stream up to 8.0MP (3840 x 2160)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

Technical Specifications

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR300	NVR301	NVR306
Product Image		HHI-E TIME GPOE	the epot
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 c	1 channel input / 1 channel output / RCA	
Video Output	1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 x SATA ports, up to 10TB each (2TB pre-installed)	2 x SATA ports, up to 10TB each (4TB pre-installed)	4 x SATA ports, up to 10TB each (2 x 4TB pre-installed)
Power Supply	48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	

Camera Mode	ı	CAM442	CAM464	
Product Image				
Image Sensor		1/2.5″ 8.0MP Progressive Scan CMOS		
Lens		2.8mm F1.6 Fixed Lens		
Min. Illuminati	on	0.04 Lux/F1.6 (Color), 0 Lux/F1.6 (IR on)		
Infrared Range 50m		50m	40m	
Lighting Comp	npensation BLC / HLC / WDR (120dB)		WDR (120dB)	
Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)		0) to CIF (352 x 288)	
Frame Rate	Main	8.0MP (1~15fps)		
	Sub	D1 (1 ~ 50fps)		
	Third	1080p (1 ~ 25fps)		
Audio Input		Built-in Microphone	N/A	
Smart Function	rt Functions Tripwire, Intrusion, Object Abandoned/Missing, Face Detection, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart I		n (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared	
Weather/Vanda	al Resist	IP67		
Power Input		12VDC / PoE (802.3af)		