



Motorised CCTV solutions.

Professional Series: 4.0MP Surveillance Kits available with 4, 8 & 16 motorised cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in Power over Ethernet for fast installations. Mix & match any equivalent priced dome or bullet camera to suit your installation needs.

- Records 4.0MP (2560 x 1440) up to real-time 25fps
- 4.0MP True WDR 30m IR motorised dome cameras
- 4.0MP True WDR 60m IR motorised bullet cameras
- Motorised lens adjustable with buttons or via NVR
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet
- Pre-installed 1TB/2TB/4TB surveillance grade HDD
- Remote view for iOS, Android & Windows Phone
 *Camera cabling sold separately



Beyond Full HD Recording & Live View



Adjustable Motorised Lens



Comprehensive Remote View



Choose from three comprehensive, ready to install packages.

The VIP Vision Professional Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.









4 Channel Professional NVR

- 4 port Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 1TB hard disk drive (additional backup via USB device or network)

4 x 4.0MP Motorised Cameras

- 2 x bullet and 2 x dome cameras
- 2.7 ~ 13.5mm (104°~28°) motorised lens
- Stream up to 4.0MP (2560 x 1440)
- · IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

8 Channel

8 Channel Professional NVR

- 8 port Extended Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 2TB hard disk drive (additional backup via USB device or network)

8 x 4.0MP Motorised Cameras

- 4 x bullet and 4 x dome cameras
- 2.7 ~ 13.5mm (104°~28°) motorised lens
- Stream up to 4.0MP (2560 x 1440)
- · IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- Camera cabling sold separately

6 Channel

16 Channel Professional NVR

- 16 port Extended Power over Ethernet NVR
- Records 4.0MP at 25fps
- Pre-installed 4TB hard disk drive (additional backup via USB device or network)

16 x 4.0MP Motorised Cameras

- 8 x bullet and 8 x dome cameras
- 2.7 ~ 13.5mm (104°~28°) motorised lens
- Stream up to 4.0MP (2560 x 1440)
- IP67 rated metal housing for outdoor use

Accessories

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

Technical Specifications

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR300	NVR301	NVR306
Product Image		HHH-T THE G	4+ ePoE
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 c	channel output / RCA	1 channel input / 2 channel output / RCA
Video Output	1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 x SATA ports, up to 10TB each (1TB pre-installed)	2 x SATA ports, up to 10TB each (2TB pre-installed)	4 x SATA ports, up to 10TB each (4TB pre-installed)
Power Supply	48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	

Camera Mode	l	CAM409	CAM410		
Product Image					
Image Sensor		1/3" 4.0MP Progressive Scan Exmor CMOS			
Lens		2.7 ~ 13.5mm F1.4 Motorised Varifocal Lens with Fixed Iris			
Min. Illuminati	on	0.03 Lux/F1.4 (Color), 0 Lux/F1.4 (IR on)			
Infrared Range		30m	60m		
Lighting Comp	ensation	BLC / HLC / WDR (120dB)			
Resolution		4.0MP (2688 x 1520) to CIF (352 x 288)			
Frame Rate Su	Main	4.0MP (1 ~ 20fps) / 3.0MP (1 ~ 25fps)			
	Sub	D1 (1 ~ 25fps)			
	Third	N/A			
Audio Input		N/A			
Smart Function	rt Functions Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		4 zones), Privacy Masking (4 zones), Smart Infrared		
Weather/Vandal Resist		IP67, IK10	IP67		
Power Input		12VDC / PoE (802.3af)			