



## Motorised CCTV solutions.

### Professional Series: 8.0MP Surveillance Kits available with 4, 8 & 16 motorised cameras

VIP Vision™ Professional Series CCTV kits offer broadcast-quality image performance with built-in Power over Ethernet for fast installations. Mix & match any equivalent priced dome or bullet camera to suit your installation needs.

- Records Ultra HD/8.0MP (3840 x 2160) up to real-time 25fps
- 8.0MP True WDR 30m IR motorised dome cameras
- 8.0MP True WDR 60m IR motorised bullet cameras
- IVS with tripwire, intrusion, motion detection & more
- Remote view in seconds with setup via QR code
- HDMI & VGA simultaneous video output
- Built-in Power over Ethernet
- Pre-installed 2TB/4TB/2 x 4TB surveillance grade HDD
- Remote view for iOS, Android & Windows Phone
  \*Camera cabling sold separately



Ultra HD Recording & Live View



**Adjustable Motorised Lens** 



**Comprehensive Remote View** 



## Choose from three comprehensive, ready to install packages.

The VIP Vision Professional Series offers complete 4, 8 and 16 channel network surveillance packages, purpose-built for rapid installation and impressive results.







#### **4 Channel Professional NVR**

- 4 port Power over Ethernet NVR
- Records 8.0MP at 25fps
- Pre-installed 2TB hard disk drive (additional backup via USB device or network)

#### 4 x 8.0MP Motorised Cameras

- 2 x bullet and 2 x dome cameras
- 3.7 ~ 11mm (112°~46°) motorised lens
- Stream up to 8.0MP (3840 x 2160)
- IP67 rated metal housing for outdoor use

### **Accessories**

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

# 8 Channel

#### 8 Channel Professional NVR

- 8 port Extended Power over Ethernet NVR
- · Records 8.0MP at 25fps
- Pre-installed 4TB hard disk drive (additional backup via USB device or network)

#### 8 x 8.0MP Motorised Cameras

- 4 x bullet and 4 x dome cameras
- 3.7 ~ 11mm (112°~46°) motorised lens
- Stream up to 8.0MP (3840 x 2160)
- IP67 rated metal housing for outdoor use

### **Accessories**

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

# 6 Channel

#### **16 Channel Professional NVR**

- 16 port Extended Power over Ethernet NVR
- Records 8.0MP at 25fps
- 2 x Pre-installed 4TB hard disk drive (additional backup via USB device or network)

#### 16 x 8.0MP Motorised Cameras

- 8 x bullet and 8 x dome cameras
- $3.7 \sim 11$ mm ( $112^{\circ} \sim 46^{\circ}$ ) motorised lens
- Stream up to 8.0MP (3840 x 2160)
- IP67 rated metal housing for outdoor use

#### **Accessories**

- CAT5 patch cable for networking: 1 x 1.5m
- HDMI output cable: 1 x 1m
- 1 x NVR Remote and 1 x Mouse
- · Camera cabling sold separately

### **Technical Specifications**

For full specifications and bracket compatibility, please see the individual unit web entry or datasheet.

NVR Model	NVR300	NVR301	NVR306
Product Image		HHI-E THIN () - ePOE	4+ ePoE
Video Input	4 channel	8 channel	16 channel
Two-way Talk	1 channel input / 1 c	1 channel input / 1 channel output / RCA	
Video Output	1 x HDMI / 1 x VGA	1 x HDMI / 1 x VGA	2 x HDMI / 2 x VGA
Maximum Resolution	Configurable from 8.0MP (3840 x 2160) to CIF	Configurable from 12.0MP (4000 x 3000) to CIF (352 x 288)	
Incoming Bandwidth	200Mbps	320Mbps	
Video Compression	H.265 / H.264	H.265 / H.264 / MJPEG / MPEG4	
Bit Rate	16 ~ 20Mbps per channel		
Alarm Input / Output	4 channels input / 2 channels relay output	4 channels input / 2 channels relay output	16 channels input / 6 channels relay output
Internal HDD	2 x SATA ports, up to 10TB each (1TB pre-installed)	2 x SATA ports, up to 10TB each (2TB pre-installed)	4 x SATA ports, up to 10TB each (4TB pre-installed)
Power Supply	48VDC, 2A	100 ~ 240VAC, 50 ~ 60Hz	

Camera Mode	I	CAM453	CAM414		
Product Image					
Image Sensor		1/2″ 8.0MP Progressive Scan CMOS			
Lens		3.7 ~ 11mm F1.9 Motorised Varifocal Lens with Fixed Iris			
Min. Illumination	on	0.004 Lux/F1.9 (Color), 0 Lux/F1.9 (IR on)			
Infrared Range		30m	60m		
<b>Lighting Comp</b>	ighting Compensation BLC / HLC / WDR (120dB)		WDR (120dB)		
Resolution	8.0MP (3840 x 2160) to CIF (352 x 288)		0) to CIF (352 x 288)		
Frame Rate	Main	8.0MP (1~25fps)			
	Sub	D1 (1 ~ 25fps)			
	Third	N/A			
Audio Input		N/A			
Smart Function	ctions Tripwire, Intrusion, Motion Detection (4 zones), Region of Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		Interest (4 zones), Privacy Masking (4 zones), Smart Infrared		
Weather/Vandal Resist		IP67, IK10	IP67		
Power Input		12VDC / PoE (802.3af)			